

INDUSTRIAL COMPONENT DATA

1SAE341111R0620 ABB Contact. ESB40-20N-06 2NA 230AC/DC

Brand: ABB | Manufacturer Part Number: 1SAE341111R0620



Manufacturer	ABB
MPN / Reference	1SAE341111R0620
Catalog number	341111
Category	Installation contactor for distribution board
Minimum order	1 Pcs
Document ID	EO-6244EDB995
Generated	2026-08-01

Product Overview

Contact. ESB40-20N-06 2NA 230AC/DC

ESB40-20N-06 Installation Contactor

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Other modular devices

Additional Product Information

Extended Product Type:ESB40-20N-06

Product ID:1SAE341111R0620

EAN:4013614518478

Catalog Description:ESB40-20N-06 Installation Contactor

Long Description:The ESB40..N installation contactors are used to control single and three-phase loads up to 40 A and can be operated by AC or DC voltages.

These contactors are made for use in household applications as well as in industrial environments.

The following benefits are provided:

Hum-free operation, low power consumption and integrated overvoltage protection.

Various contact combinations and accessories are available.

Ordering

Package Level 1 EAN:4013614524783

Minimum Order Quantity:1 piece

Customs Tariff Number:85365080

Popular Downloads

Instructions and Manuals:2CDC103043M6801

Dimensions

Product Net Width:54mm

Product Net Height:85mm

Product Net Depth / Length:65mm

Product Net Weight:0.37kg

Technical

Rated Operational Voltage:Main Circuit 220 V DC

Main Circuit 400 V AC

Rated Control Circuit Voltage (Uc):230 V

Rated Frequency (f):Control Circuit 400 Hz

Control Circuit 50 Hz

Control Circuit 60 Hz

Control Circuit DC

Main Circuit 50 Hz

Main Circuit 60 Hz

Main Circuit DC

Rated Operational Current AC-1 (Ie):(NO) 40 A

Rated Operational Current AC-3 (Ie):(230 V) Single Phase, NO 22 A

Rated Operational Power AC-1 (Pe):(230 V) Single Phase, NO 9.2 kW

Rated Operational Power AC-3 (Pe):(230 V) Single Phase, NO 3.7 kW

Rated Operational Current AC-7a (Ie):(NO) 40 A

Rated Operational Power AC-7a (Pe):(230 V) Single Phase, NO 9.2 kW

Rated Opera...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SAE341111R0620 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.