

INDUSTRIAL COMPONENT DATA

1SAL101915R9902 ABB MC2A400ATY Mini Contactor

Brand: ABB | Manufacturer Part Number: 1SAL101915R9902



Manufacturer	ABB
MPN / Reference	1SAL101915R9902
Catalog number	101915
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-6F9D168566
Generated	2026-08-01

Product Overview

MC2A400ATY Mini Contactor

The MC2A400ATY mini contactor is a dimension optimized 4 pole contactor with screw terminals. This device is a great solution when high performances are needed but the space is limited. Mini contactors are used in residential buildings, commercial buildings and industrial applications for the control of single or three-phase loads up to 5.5 kW (AC-3) and 20 A / 690 V (AC-1) or switching of control signals. The product is suitable for wall or rail mounting.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	ABB > Contactors and overload relays
--------------	--------------------------------------

Additional Product Information

b'

General Information

Extended Product Type:MC2A400ATYProduct ID:1SAL101915R9902EAN:4013614544408Catalog

Description:MC2A400ATY Mini Contactor 4NO 500V 50Hz/600V 60HzLong Description:The MC2A400ATY mini contactor is a dimension optimized 4 pole contactor with screw terminals. This device is a great solution when high performances are needed but the space is limited. Mini contactors are used in residential buildings, commercial buildings and industrial applications for the control of single or three-phase loads up to 5.5 kW (AC-3) and 20 A / 690 V (AC-1) or switching of control signals. The product is suitable for wall or rail mounting.

Ordering

Minimum Order Quantity:1 pieceCustoms Tariff Number:85365080Popular Downloads

Instructions and Manuals:\n2CDC103061M6801Dimensions

Product Net Width:45 mmProduct Net Height:48 mmProduct Net Depth / Length:56 mmProduct Net Weight:0.17 kgTechnical

Number of Poles:4Mini Contactor Type:Mini ContactorRated Operational Voltage:Main Circuit 690 V AC
Main Circuit 440 V DCRated Frequency (f):Control Circuit 50 Hz
Control Circuit 60 Hz
Main Circuit 50 Hz
Main Circuit 60 Hz
Main Circuit DCRated Impulse Withstand Voltage (Uimp):Main Circuit 6 kVRated Insulation Voltage (Ui):750 VNumber of
Main Contacts NC:0Number of Main Contacts NO:4Rated Operational Current AC-1 (Ie):(690 V) 55 °C 20 A
(690 V) 70 °C 16 A
(230 V) 55 °C 20 A
(230 V) 70 °C 16 A
(400 V) 55 °C 20 A
(400 V) 70 °C 16 A
(500 V) 55 °C 20 A
(500 V) 70 °C 16 ARated Operational Power AC-3...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SAL101915R9902 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.