

INDUSTRIAL COMPONENT DATA

1SAM350010R1014 ABB MS132-25K Push-In Motor Guard

Brand: ABB | Manufacturer Part Number: 1SAM350010R1014



Manufacturer	ABB
MPN / Reference	1SAM350010R1014
Catalog number	350010
Category	Motor protection circuit-breaker
Minimum order	1 Pcs
Document ID	EO-C03CDA718B
Generated	2026-08-01

Product Overview

MS132-25K Push-In Motor Guard

MS132-25K motor protection circuit breaker Push-In

MS132-25K Manual Motor Starter 20 ... 25 A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Electronic motor protection relays

Additional Product Information

Ordering

Minimum Order Quantity 1 piece

Customs Tariff Number 85362010

Popular Downloads

Data Sheet, Technical Information 1SBC100212C0203

Instructions and Manuals 2CDC131120M6801

Instructions and Manuals (Part 2) 2CDC131060M0202

Ex Operating Instructions 2CDC131063M6801

Time-Current Characteristic Curve 1SAM300505F0014

I²t Characteristic 1SAM300507F0001

1SAM300507F0003

Cut-off Current Characteristic 1SAM300508F0001

1SAM300508F0003

CAD Dimensional Drawing 2CDC001079B0201

Installation Video 9AKK108466A6074

9AKK108466A6068

Marketing Video 9AKK107991A4712

2CDC131153V0201

Dimensions

Product Net Width 45 mm

Product Net Height 112 mm

Product Net Depth / Length 87 mm

Product Net Weight 0.316 kg

Technical

Rated Service Short-Circuit Breaking Capacity (Ics) (230 V AC) 50 kA

(250 V DC) 3 Poles in Series 10 kA

(400 V AC) 50 kA

(440 V AC) 30 kA

(500 V AC) 10 kA

(690 V AC) 3 kA

Rated Ultimate Short-Circuit Breaking Capacity (Icu) (230 V AC) 50 kA

(400 V AC) 50 kA

(440 V AC) 30 kA

(500 V AC) 10 kA

(690 V AC) 3 kA

Rated Instantaneous Short-Circuit Current Setting (Ii) 375 A

Setting Range 20 ... 25 A

Rated Operational Power AC-3 (Pe) (400 V) Three Phase 11 kW

Rated Operational Power AC-3e (Pe) (400 V) Three Phase 11 kW

Rated Operational Voltage Main Circuit 690 V AC

Main Circuit 250 V DC

Rated Operational Current (Ie) 25 A

Rated Operational Current AC-3 (Ie) 25 A

Rated Operational Current AC-3e (Ie) 25 A

Rated Operational Current DC-5 (Ie) 25 A

Rated Frequency (f) Main Circuit 50 Hz

Main Ci...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SAM350010R1014 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.