

INDUSTRIAL COMPONENT DATA

1SBH131001R8039 ABB NFC33/11-80 Contactor

Brand: ABB | Manufacturer Part Number: 1SBH131001R8039



Manufacturer	ABB
MPN / Reference	1SBH131001R8039
Catalog number	131001
Category	Contactor relay
Minimum order	1 Pcs
Document ID	EO-EF5333F6AC
Generated	2026-07-28

Product Overview

NFC33/11-80 Contactor

NFC33/11-80 220-230V50Hz 230-240V60Hz Contactor Relay

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Contactors and overload relays

Additional Product Information

Ordering

Minimum Order Quantity 1 piece

Customs Tariff Number 85364900

Popular Downloads

Data Sheet, Technical Information 1SBC100219C0201

Instructions and Manuals 1SBC101027M6801

Instructions and Manuals (Part 2) 1SAC200017M0002

CAD Dimensional Drawing 2CDC001079B0201

Dimensions

Product Net Width 45 mm

Product Net Depth / Length 110.5 mm

Product Net Height 86 mm

Product Net Weight 0.358 kg

Technical

Number of Main Contacts NO 0

Number of Main Contacts NC 0

Number of Auxiliary Contacts NO 4

Number of Auxiliary Contacts NC 4

Number of Poles 8P

Standards IEC/EN 60947-1, IEC/EN 60947-5-1, UL 60947-1, UL 60947-5-1, CSA C22.2 No. 60947-1-13, CSA C22.2 No. 60947-5-1-14

Rated Operational Voltage Auxiliary Circuit 690 V

Rated Frequency (f) Auxiliary Circuit 50 / 60 Hz

Control Circuit 50 / 60 Hz

Main Circuit 50 / 60 Hz

Conventional Free-air Thermal Current (Ith) acc. to IEC 60947-5-1, $\theta = 40^\circ\text{C}$ 16 A

Rated Operational Current AC-15 (Ie) (500 V) 2 A

(690 V) 2 A

(24 / 127 V) 6 A

(220 / 240 V) 4 A

(400 / 440 V) 3 A

Rated Operational Current DC-13 (Ie) (24 V) 6 A / 144 W

(48 V) 2.8 A / 134 W

(72 V) 1 A / 72 W

(110 V) 0.55 A / 60 W

(125 V) 0.55 A / 69 W

(220 V) 0.27 A / 60 W

(250 V) 0.27 A / 68 W

(400 V) 0.15 A / 60 W

(500 V) 0.13 A / 65 W

(600 V) 0.1 A / 60 W

Rated Short-time Withstand Current Low Voltage (Icw) for 0.1 s 140 A
for 1 s 100 A

Rated Insulation Voltage (Ui) acc. to IEC 60947-5-1 690 V

acc. to UL/CSA 600 V

Rated Impulse Withstand Voltage (Uimp) 6 kV

Maximum Electrical Switchin...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SBH131001R8039 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.