

**INDUSTRIAL COMPONENT DATA**

# 1SBK134238R1100 ABB DRAF09-11U 24-60V50/60HZ DRAF09-11U

Brand: ABB | Manufacturer Part Number: 1SBK134238R1100



|                 |                                       |
|-----------------|---------------------------------------|
| Manufacturer    | ABB                                   |
| MPN / Reference | 1SBK134238R1100                       |
| Catalog number  | 134238                                |
| Category        | Enclosure for control circuit devices |
| Minimum order   | 1 Pcs                                 |
| Document ID     | EO-557D995D47                         |
| Generated       | 2026-08-02                            |

## Product Overview

DRAF09-11U 24-60V50/60HZ DRAF09-11U  
DRAF09-11U BOOTS IN BOX 24-60VAC/DC  
DRAF09-11U 24-60V50/60HZ Contactor Starter

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                      |
|--------------|--------------------------------------|
| Catalog path | ABB > Contactors and overload relays |
|--------------|--------------------------------------|

## Additional Product Information

**Ordering**

Minimum Order Quantity 1 piece

Customs Tariff Number 85364900

Product Main Type DRAF09

**Popular Downloads**

Data Sheet, Technical Information 1SBC100214C0202

Instructions and Manuals 1SBC101048M6801

Instructions and Manuals (Part 2) 1SAC200017M0002

CAD Dimensional Drawing 2CDC001079B0201

**Dimensions**

Product Net Width 107 mm

Product Net Depth / Length 131 mm

Product Net Height 230 mm

Product Net Weight 0.82 kg

#### Technical

Coil Consumption Holding at Max. Rated Control Circuit Voltage 60 Hz 24 V·A

Connecting Capacity Auxiliary Circuit Flexible with Ferrule 1/2x 0.75 ... 2.5 mm<sup>2</sup>

Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm<sup>2</sup>

Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm<sup>2</sup>

Rigid Solid 1/2x 1 ... 2.5 mm<sup>2</sup>

Rigid Stranded 1/2x 1 ... 2.5 mm<sup>2</sup>

Connecting Capacity Control Circuit Flexible with Ferrule 1/2x 0.75 ... 2.5 mm<sup>2</sup>

Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm<sup>2</sup>

Flexible with Insulated Ferrule 1x 0.75 ... 1.5 mm<sup>2</sup>

Rigid Solid 1/2x 1 ... 2.5 mm<sup>2</sup>

Rigid Stranded 1/2x 1 ... 2.5 mm<sup>2</sup>

Connecting Capacity Main Circuit Flexible with Ferrule 1/2x 0.75 ... 6 mm<sup>2</sup>

Flexible with Insulated Ferrule 1x 0.75 ... 4 mm<sup>2</sup>

Flexible with Insulated Ferrule 2x 0.75 ... 2.5 mm<sup>2</sup>

Rigid Solid 1/2x 1 ... 4 mm<sup>2</sup>

Rigid Stranded 1/2x 1 ... 6 mm<sup>2</sup>

Housing Material ABS

Number of Auxiliary Contacts NC 0

Number of Auxiliary Contacts NO 1

Number of Main Contacts NC 0

Number of Main Contacts NO 3

Number of Poles 3P

Pollution Degree 3

Rated Control Circuit Voltage (Uc) 50 Hz 24 ... 60 V

60 Hz 24 ... 60 V

D...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SBK134238R1100 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

#### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.