

INDUSTRIAL COMPONENT DATA

1SBK174238R1400 ABB DRAF16-14U STARTS IN BOX 250-500VAC/DC

Brand: ABB | Manufacturer Part Number: 1SBK174238R1400



Manufacturer	ABB
MPN / Reference	1SBK174238R1400
Catalog number	174238
Category	Enclosure for control circuit devices
Minimum order	1 Pcs
Document ID	EO-EB20663E74
Generated	2026-08-02

Product Overview

DRAF16-14U STARTS IN BOX 250-500VAC/DC
DRAF16-14U 250-500V50/60HZ Contactor Starter

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	ABB > Contactors and overload relays
--------------	--------------------------------------

Additional Product Information

Ordering

Minimum Order Quantity 1 piece

Customs Tariff Number 85364900

Product Main Type DRAF16

Popular Downloads

Data Sheet, Technical Information 1SBC100214C0202

Instructions and Manuals 1SBC101048M6801

Instructions and Manuals (Part 2) 1SAC200017M0002

CAD Dimensional Drawing 2CDC001079B0201

Dimensions

Product Net Width 107 mm

Product Net Depth / Length 131 mm

Product Net Height 230 mm

Product Net Weight 0.82 kg

Technical

Coil Consumption Holding at Max. Rated Control Circuit Voltage 60 Hz 250 V·A
Connecting Capacity Auxiliary Circuit Flexible with Ferrule 1/2x 0.75 ... 2.5 mm²
Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm²
Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm²
Rigid Solid 1/2x 1 ... 2.5 mm²
Rigid Stranded 1/2x 1 ... 2.5 mm²
Connecting Capacity Control Circuit Flexible with Ferrule 1/2x 0.75 ... 2.5 mm²
Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm²
Flexible with Insulated Ferrule 1x 0.75 ... 1.5 mm²
Rigid Solid 1/2x 1 ... 2.5 mm²
Rigid Stranded 1/2x 1 ... 2.5 mm²
Connecting Capacity Main Circuit Flexible with Ferrule 1/2x 0.75 ... 6 mm²
Flexible with Insulated Ferrule 1x 0.75 ... 4 mm²
Flexible with Insulated Ferrule 2x 0.75 ... 2.5 mm²
Rigid Solid 1/2x 1 ... 4 mm²
Rigid Stranded 1/2x 1 ... 6 mm²
Housing Material ABS
Number of Auxiliary Contacts NC 0
Number of Auxiliary Contacts NO 1
Number of Main Contacts NC 0
Number of Main Contacts NO 3
Number of Poles 3P
Pollution Degree 3
Rated Control Circuit Voltage (Uc) 50 Hz 250 ... 500 V
60 Hz 250 ... 50...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SBK174238R1400 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.