

**INDUSTRIAL COMPONENT DATA**

# 1SBL171022R8610 ABB UAFC15-30-10-86 Cont.Cond. 15kVAr 415V

Brand: ABB | Manufacturer Part Number: 1SBL171022R8610



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | ABB                 |
| MPN / Reference | 1SBL171022R8610     |
| Catalog number  | 171022              |
| Category        | Capacitor contactor |
| Minimum order   | 1 Pcs               |
| Document ID     | EO-98AB4CA8F3       |
| Generated       | 2026-08-01          |

## Product Overview

UAFC15-30-10-86 Cont.Cond. 15kVAr 415V

UAFC15-30-10-86 400-415V 50Hz 415-440V 60Hz Contactor

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      ABB &gt; Contactors and overload relays

## Additional Product Information

**Ordering**

Minimum Order Quantity 1 piece

Customs Tariff Number 85364900

**Popular Downloads**

Data Sheet, Technical Information 1SBC100214C0202

Data Sheet, Technical Information (Part 2) 1SFC100125C0334

Instructions and Manuals 1SBC101082M6811

Instructions and Manuals (Part 2) 1SBC101082M6801

CAD Dimensional Drawing 2CDC001079B0201

**Dimensions**

Product Net Width 45 mm

Product Net Depth / Length 77 mm

Product Net Height 86 mm

Product Net Weight 0.323 kg

**Technical**

Number of Main Contacts NO 3

Number of Main Contacts NC 0

Number of Auxiliary Contacts NO 1

Number of Auxiliary Contacts NC 0

Number of Poles 3P

Standards IEC 60947-1 / 60947-4-1 and EN 60947-1 / 60947-4-1

Rated Operational Voltage Auxiliary Circuit 690 V

Main Circuit 690 V

Rated Frequency (f) Auxiliary Circuit 50 / 60 Hz

Control Circuit 50 / 60 Hz

Main Circuit 50 / 60 Hz

Rated Operational Current AC-15 (Ie) (500 V) 2 A

(690 V) 2 A

(24 / 127 V) 6 A

(220 / 240 V) 4 A

(380 / 400 V) 3 A

Rated Operational Current DC-13 (Ie) (24 V) 6 A / 144 W

(48 V) 2.8 A / 134 W

(72 V) 1 A / 72 W

(110 V) 0.55 A / 60 W

(125 V) 0.55 A / 69 W

(220 V) 0.27 A / 60 W

(250 V) 0.27 A / 68 W

Rated Operational Power AC-6b (Pe) (230 / 240 V) 40 °C, 50 / 60 Hz 8.7 kvar

(230 / 240 V) 60 °C, 50 / 60 Hz 6.7 kvar

(230 / 240 V) 70 °C, 50 / 60 Hz 5.7 kvar

(400 / 415 V) 40 °C, 50 / 60 Hz 15 kvar

(400 / 415 V) 70 °C, 50 / 60 Hz 11.7 kvar

(400 / 415 V) 60 °C, 50 / 60 Hz 10 kvar

(440 V) 40 °C, 50 / 60 Hz 15.5 kvar

(440 V) 60 °C, 50 / 60 Hz 12.7 kvar

(440 V) 70 °C,....

**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**

Send ABB / 1SBL171022R8610 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.