INDUSTRIAL COMPONENT DATA

1SBL271024R7510 ABB UAFC25-30-10RA-75 Cont.Cond. 25kVAr 200V

Brand: ABB | Manufacturer Part Number: 1SBL271024R7510

Manufacturer	ABB
MPN / Reference	1SBL271024R7510
Catalog number	271024
Category	Capacitor contactor
Minimum order	1 Pcs
Document ID	EO-51828C5FAC
Generated	2026-08-04

Product Overview

UAFC25-30-10RA-75 Cont.Cond. 25kVAr 200V
UAFC25-30-10RA-75 200V 50Hz 200-220V 60Hz Contactor

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	ABB > Contactors and overload relays

Additional Product Information

Ordering
Minimum Order Quantity 1 piece
Customs Tariff Number 85364900
Popular Downloads
Data Sheet, Technical Information 1SBC100214C0202
Data Sheet, Technical Information (Part 2) 1SFC100125C0334
Instructions and Manuals 1SBC101082M6811
Instructions and Manuals (Part 2) 1SBC101082M6801
CAD Dimensional Drawing 2CDC001079B0201
Dimensions
Product Net Width 45 mm
Product Net Depth / Length 119.7 mm
Product Net Height 140.7 mm
Product Net Weight 0.427 kg

Technical
Number of Main Contacts NO 3
Number of Main Contacts NC 0
Number of Auxiliary Contacts NO 1
Number of Auxiliary Contacts NC 0
Number of Poles 3P
Standards IEC 60947-1 / 60947-4-1 and EN 60947-1 / 60947-4-1
Rated Operational Voltage Auxiliary Circuit 690 V
Main Circuit 690 V
Rated Frequency (f) Auxiliary Circuit 50 / 60 Hz
Control Circuit 50 / 60 Hz
Main Circuit 50 / 60 Hz
Rated Operational Current AC-15 (Ie) (500 V) 2 A
(690 V) 2 A
(24 / 127 V) 6 A
(220 / 240 V) 4 A
(380 / 400 V) 3 A
Rated Operational Current DC-13 (Ie) (24 V) 6 A / 144 W
(48 V) 2.8 A / 134 W
(72 V) 1 A / 72 W
(110 V) 0.55 A / 60 W
(125 V) 0.55 A / 69 W
(220 V) 0.27 A / 60 W
(250 V) 0.27 A / 68 W
Rated Operational Power AC-6b (Pe) (230 / 240 V) 40 °C, 50 / 60 Hz 14.5 kvar
(230 / 240 V) 60 °C, 50 / 60 Hz 12 kvar
(230 / 240 V) 70 °C, 50 / 60 Hz 10.5 kvar
(400 / 415 V) 40 °C, 50 / 60 Hz 25 kvar
(400 / 415 V) 70 °C, 50 / 60 Hz 21 kvar
(400 / 415 V) 60 °C, 50 / 60 Hz 18 kvar
(440 V) 40 °C, 50 / 60 Hz 27.5 kvar
(440 V) 60 °C, 50 / 60 Hz 23 kvar
(440 V) 70 °...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SBL271024R7510 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.