

**INDUSTRIAL COMPONENT DATA****1SBL371074R3611 ABB AX65-30-11-36 220V60Hz 190V50Hz**

Brand: ABB | Manufacturer Part Number: 1SBL371074R3611



|                 |                               |
|-----------------|-------------------------------|
| Manufacturer    | ABB                           |
| MPN / Reference | 1SBL371074R3611               |
| Catalog number  | 371074                        |
| Category        | Power contactor, AC switching |
| Minimum order   | 1 Pcs                         |
| Document ID     | EO-0FF3064137                 |
| Generated       | 2026-08-04                    |

**Product Overview**

AX65-30-11-36 220V60Hz 190V50Hz

AX65-30-11-36 190V50Hz/220V60Hz Contactor

**STRUCTURED PRODUCT DATA****Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

**Classification & Catalog Path**Catalog path **ABB > Contactors and overload relays****Additional Product Information**

## Ordering

Minimum Order Quantity 1 piece

Customs Tariff Number 85364900

## Popular Downloads

EPLAN Data 9AAC177931\_EPLAN

Data Sheet, Technical Information 1SBC100187L0203

Instructions and Manuals 9AKK107492A7059

CAD Dimensional Drawing 2CDC001079B0201

## Dimensions

Product Net Width 82 mm

Product Net Depth / Length 110 mm

Product Net Height 108 mm

Product Net Weight 1.05 kg

## Technical

Number of Main Contacts NO 3

Number of Main Contacts NC 0  
Number of Auxiliary Contacts NO 1  
Number of Auxiliary Contacts NC 1  
Rated Operational Voltage Auxiliary Circuit 690 V  
Main Circuit 690 V  
Rated Frequency (f) Auxiliary Circuit 50 / 60 Hz  
Main Circuit 50 / 60 Hz  
Conventional Free-air Thermal Current (I<sub>th</sub>) acc. to IEC 60947-4-1, Open Contactors ? = 40 °C 125 A  
Rated Operational Current AC-1 (I<sub>e</sub>) (220 / 240 V) 55 °C 95 A  
(690 V) 40 °C 115 A  
(690 V) 70 °C 80 A  
Rated Operational Current AC-3 (I<sub>e</sub>) (415 V) 55 °C 65 A  
(440 V) 55 °C 65 A  
(500 V) 55 °C 55 A  
(690 V) 55 °C 43 A  
(380 / 400 V) 55 °C 65 A  
(220 / 230 / 240 V) 55 °C 65 A  
Rated Operational Power AC-3 (P<sub>e</sub>) (415 V) 37 kW  
(440 V) 37 kW  
(500 V) 37 kW  
(690 V) 37 kW  
(380 / 400 V) 30 kW  
(220 / 230 / 240 V) 18.5 kW  
Rated Short-time Withstand Current Low Voltage (I<sub>cw</sub>) at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 650 A  
at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 135 A  
at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 250 A  
at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 1000 A  
at 40 °C Ambient Temp, in Free...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SBL371074R3611 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.