

INDUSTRIAL COMPONENT DATA

1SCA022700R6340 ABB Int. Boxed disconnecter OT200KUUR3AZ

Brand: ABB | Manufacturer Part Number: 1SCA022700R6340



Manufacturer	ABB
MPN / Reference	1SCA022700R6340
Catalog number	022700
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-8C9D86CAAD
Generated	2026-08-03

Product Overview

Int. Boxed disconnecter OT200KUUR3AZ

OT200KUUR3AZ EMC safety switch

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Manual Switches

Additional Product Information

Circular Value

Conflict Minerals Reporting Template (CMRT) 9AKK108467A5658

REACH Declaration 1SCC340076D0201

RoHS Information 1SCC340075D0201

Toxic Substances Control Act - TSCA 1SCC340095D0201

Ordering

Minimum Order Quantity 1 piece

Customs Tariff Number 85363090

Country of Origin Finland (FI)

Popular Downloads

Data Sheet, Technical Information 1SCC340015C0201

Instructions and Manuals 1SCC340016M0005

Mechanical Drawings OTKM604023PBL4R.stp

Dimensions

Product Net Width 400 mm

Product Net Height 600 mm

Product Net Depth / Length 230 mm

Product Net Weight 21.91 kg

Technical

Rated Operational Current AC-22A (Ie) (380 ... 415 V) 200 A

(500 V) 200 A

(690 V) 200 A

Rated Operational Current AC-23A (Ie) (380 ... 415 V) 200 A

(500 V) 200 A

(690 V) 200 A

Rated Operational Power AC-23A (Pe) (380 ... 415 V) 110 kW

(500 V) 132 kW

(690 V) 160 kW

Conventional Thermal Current (Ithe) Fully Enclosed 200 A

Rated Impulse Withstand Voltage (Uimp) 8 kV

Rated Insulation Voltage (Ui) acc. to IEC/EN 60664-1 1000 V

Rated Operational Voltage Main Circuit 1000 V

Rated Short-Circuit Making Capacity (Icm) (1000 V AC) 30 kA

Rated Short-time Withstand Current Low Voltage (Icw) for 1 s 8 kA

Rated Conditional Short-Circuit Current (Inc) 40.5 kA

Power Loss at Rated Operating Conditions per Pole 4 W

Pollution Degree 3

Handle Color Red / Yellow

Handle Type Pistol handle

Standards IEC 60947-1, -3

Special Functions EMC

Number of Poles 3

Neutral Type No neutral terminal

Connecting Capacity Main Circuit Hole Diamet...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SCA022700R6340 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.