

INDUSTRIAL COMPONENT DATA

1SCA022757R3690 ABB Disconnecter Switch OT200U11

Brand: ABB | Manufacturer Part Number: 1SCA022757R3690



Manufacturer	ABB
MPN / Reference	1SCA022757R3690
Catalog number	022757
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-CA6DC39FB2
Generated	2026-07-29

Product Overview

Disconnecter Switch OT200U11
OT200U11 SWITCH-DISCONNECTOR

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	ABB > Manual Switches
--------------	-----------------------

Additional Product Information

ABB EcoSolutions
End Of Life Disassembling Instructions 1SCC301117M0201
Environmental Information 1SCC301265D0201
Environmental Product Declaration - EPD 1SCC301282D0201
Material Compliance
Conflict Minerals Reporting Template (CMRT) 9AKK108467A5658
REACH Declaration 1SCC011021D0201
RoHS Declaration 1SCC011020D0201
RoHS Information Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA 1SCC011025D0201
Popular Downloads
Data Sheet, Technical Information 1SCC301020C0201
Instructions and Manuals 1SCC301031M0220
Mechanical Drawings 1SCC301242F0001
1SCC301241F0001

OT200-250U11.stp

OT200-250U11.igs

Environmental

Degree of Protection Front IP00

Pollution Degree 3

Ordering

Minimum Order Quantity 1 piece

Customs Tariff Number 85365080

Country or Territory of Origin Finland

Dimensions

Product Net Width 131.5 mm

Product Net Height 170 mm

Product Net Depth / Length 82.5 mm

Product Net Weight 1 kg

Container Information

Package Level 1 Units box 1 piece

Package Level 1 Width 190 mm

7.5 in

Package Level 1 Depth / Length 290 mm

11.4 in

Package Level 1 Height 110 mm

4.3 in

Package Level 1 Gross Weight 1.2 kg

2.6 lb

Package Level 1 EAN 6417019246642

Technical

Conventional Thermal Current (I_{the}) Fully Enclosed 200 A

Distance Between Phases Standard

Mechanical Durability 20000

Mounting Type Base mounting

Number of Poles 2P

Operating Mode Front

Power Loss at Rated Operating Conditions per Pole 6.5 W

Rated Impulse Withstand Voltage (U_{imp}) 12 kV....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SCA022757R3690 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.