

INDUSTRIAL COMPONENT DATA

1SCA109444R1001 ABB OT60FT4N2 disconnect switch

Brand: ABB | Manufacturer Part Number: 1SCA109444R1001



Manufacturer	ABB
MPN / Reference	1SCA109444R1001
Catalog number	109444
Category	Switch disconnector
Minimum order	1 Pcs
Document ID	EO-8367AC4934
Generated	2026-08-01

Product Overview

OT60FT4N2 disconnect switch
Switch disconnector OT60FT4N2
OT60FT4N2 SWITCH-DISCONNECTOR

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	ABB > Manual Switches
--------------	-----------------------

Additional Product Information

ABB EcoSolutions
Environmental Product Declaration - EPD 1SCC301280D0201
Material Compliance
Conflict Minerals Reporting Template (CMRT) 9AKK108467A5658
REACH Declaration 1SCC011021D0201
RoHS Declaration 1SCC011020D0201
RoHS Information Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA 1SCC011025D0201
Popular Downloads
Data Sheet, Technical Information No documentation needed
Instructions and Manuals 1SCC301060M0004
Mechanical Drawings 1SCC301472F0001
1SCC301471F0001
OT100-125FT4N2.igs

Environmental Product Declaration - EPD 1SCC301280D0201

Environmental

Degree of Protection Front IP20

Pollution Degree 3

Ordering

Minimum Order Quantity 1 piece

Customs Tariff Number 85365080

Country or Territory of Origin Finland

Dimensions

Product Net Width 96.5 mm

Product Net Height 100 mm

Product Net Depth / Length 66.5 mm

Product Net Weight 0.5 kg

Container Information

Package Level 1 Units box 1 piece

Package Level 1 Width 109 mm

Package Level 1 Depth / Length 112 mm

Package Level 1 Height 79 mm

Package Level 1 Gross Weight 0.56 kg

Package Level 1 EAN 6417019426433

Technical

Cable Cross-Section Cu 2.5 ... 25 mm²

Connecting Capacity Main Circuit Flexible 1x Cu 2.5...25 mm²

Stranded 1x Cu 2.5...25 mm²

Degree of Protection Front IP20

Handle Type Handle and shaft not included

Mechanical Durability 20000

Mounting Type Door mounting

Number of Poles 4P

Pollution Degree 3

Power Loss at Rated Operating Conditions per Pole 1.6 W

Rated Impulse Wi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SCA109444R1001 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.