

INDUSTRIAL COMPONENT DATA

1SCA117316R1001 ABB Disconnect interurptor OT2000U04

Brand: ABB | Manufacturer Part Number: 1SCA117316R1001



Manufacturer	ABB
MPN / Reference	1SCA117316R1001
Catalog number	117316
Category	Switch disconnector
Minimum order	1 Pcs
Document ID	EO-E172AD193C
Generated	2026-08-02

Product Overview

Disconnect interurptor OT2000U04
OT2000U04 SWITCH-DISCONNECTOR

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	ABB > Manual Switches
--------------	-----------------------

Additional Product Information

ABB EcoSolutions
End Of Life Disassembling Instructions 1SCC301120M0201
Environmental Product Declaration - EPD 1SCC301300D0201
Material Compliance
Conflict Minerals Reporting Template (CMRT) 9AKK108467A5658
REACH Declaration 1SCC011021D0201
RoHS Declaration 1SCC011020D0201
RoHS Information Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA 1SCC011025D0201
Popular Downloads
Data Sheet, Technical Information 1SCC301020C0201
Instructions and Manuals 1SCC301094M0203
Mechanical Drawings 1SCC307538F0201OT1600-2000U04.igs
Environmental
Degree of Protection Front IP00

Pollution Degree 3

Ordering

Minimum Order Quantity 1 piece

Customs Tariff Number 85365080

Country or Territory of Origin Finland

Dimensions

Product Net Width 615 mm

Product Net Height 546 mm

Product Net Depth / Length 415 mm

Product Net Weight 68.9 kg

Container Information

Package Level 1 Units box 1 piece

Package Level 1 Width 420 mm

Package Level 1 Depth / Length 650 mm

Package Level 1 Height 620 mm

Package Level 1 Gross Weight 72.1 kg

Package Level 1 EAN 6417019493350

Technical

Distance Between Phases Standard

Fourth Pole Position Right Side

Fourth Pole Type Switched - Simultaneous Function

Mechanical Durability 2500

Mounting Type Base mounting

Number of Poles 4P

Operating Mode Front

Position of Line Terminals Top In - Bottom Out

Bottom In - Top Out

Power Loss at Rated Operating Conditions per Pole 96 W

Rated Impulse Withstand Voltage (Uimp) 12 kV

Rated Operat...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SCA117316R1001 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.