

INDUSTRIAL COMPONENT DATA

1SCA125129R1001 ABB Disconnecter switch box OTDCP16S11M

Brand: ABB | Manufacturer Part Number: 1SCA125129R1001



Manufacturer	ABB
MPN / Reference	1SCA125129R1001
Catalog number	125129
Category	Switch disconnector
Minimum order	1 Pcs
Document ID	EO-4C0DD58DF0
Generated	2026-07-31

Product Overview

Disconnecter switch box OTDCP16S11M

OTDCP16S11M Enclosed solar switch

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **ABB > Manual Switches**

Additional Product Information

Material Compliance

Conflict Minerals Reporting Template (CMRT) 9AKK108467A5658

REACH Declaration 1SCC301240D0201

RoHS Declaration 1SCC301239D0201

RoHS Information Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Toxic Substances Control Act - TSCA 1SCC301321D0201

Popular Downloads

Data Sheet, Technical Information 1SCC340015C0201

Instructions and Manuals 1SCC340027M0002

Mechanical Drawings OTDCK159595SM20.stp

Environmental

Degree of Protection acc. to IEC 60529 IP65

Pollution Degree 3

Ordering

Minimum Order Quantity 1 piece

Customs Tariff Number 85365080

Country or Territory of Origin Finland

Dimensions

Product Net Width 95 mm

Product Net Height 150 mm

Product Net Depth / Length 95 mm

Product Net Weight 0.55 kg

Container Information

Package Level 1 Units box 1 piece

Package Level 1 Width 142 mm

Package Level 1 Depth / Length 167 mm

Package Level 1 Height 108 mm

Package Level 1 Gross Weight 0.6 kg

Package Level 1 EAN 6417019553856

Technical

Cable Entry Position Up/Down

Cable Outlets Per Side 2xM20 / 2xM20

Connecting Capacity Main Circuit Screw Clamp 2.5...16 mm²

Conventional Thermal Current (I_{the}) Fully Enclosed 16 A

Degree of Protection acc. to IEC 60529 IP65

Enclosure Material Plastic

Handle Color Black

Handle Type Selector handle

Mounted Auxiliary Contacts 0 NO, 0 NC

Mounting Type Base mounting

Number of Poles 2P

Pollution Degree 3

Power Loss at Rated Operating Conditions per Pole 0.15 W

Rated Impulse Withstand Voltage (U_{imp}) 8 kV

Rated Insulation Volt...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SCA125129R1001 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.