

INDUSTRIAL COMPONENT DATA

1SCA161768R1001 ABB Disconnecter switch OT2000EC04P

Brand: ABB | Manufacturer Part Number: 1SCA161768R1001



Manufacturer	ABB
MPN / Reference	1SCA161768R1001
Catalog number	161768
Category	Switch disconnector
Minimum order	1 Pcs
Document ID	EO-53228B8C84
Generated	2026-08-01

Product Overview

Disconnecter switch OT2000EC04P
OT2000EC04P SWITCH-DISCONNECTOR

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **ABB > Manual Switches**

Additional Product Information

ABB EcoSolutions
End Of Life Disassembling Instructions 1SCC301120M0201
Environmental Information 1SCC301233D0201
Environmental Product Declaration - EPD 1SCC301300D0201
Material Compliance
Conflict Minerals Reporting Template (CMRT) 9AKK108467A5658
REACH Declaration 1SCC011021D0201
RoHS Declaration 1SCC011020D0201
RoHS Information Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA 1SCC011025D0201
Popular Downloads
Data Sheet, Technical Information No documentation needed
Instructions and Manuals 1SCC301047M0213
Mechanical Drawings 1SCC301504F0001
1SCC301503F0001

OT1600E04.igs

Environmental Product Declaration - EPD 1SCC301300D0201

Environmental

Environmental Information 1SCC301233D0201

Pollution Degree 3

Ordering

Minimum Order Quantity 1 piece

Customs Tariff Number 85365080

Country or Territory of Origin Finland

Dimensions

Product Net Width 414.5 mm

Product Net Height 372 mm

Product Net Depth / Length 167 mm

Product Net Weight 22.3 kg

Container Information

Package Level 1 Units box 1 piece

Package Level 1 Width 170 mm

Package Level 1 Depth / Length 400 mm

Package Level 1 Height 435 mm

Package Level 1 Gross Weight 23.3 kg

Package Level 1 EAN 6417019918556

Technical

Conventional Free-air Thermal Current (I_{th}) ? = 40 °C 2000 A

Handle Type Handle and shaft included

Mechanical Durability 6000

Number of Poles 4P

Pollution Degree 3

Power Loss at Rated Operating Conditions per Pole 48 W

Rated Conditional Short-Circuit Current....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SCA161768R1001 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.