

INDUSTRIAL COMPONENT DATA

1SCA162963R1001 ABB Int. Sec. for 800-1000VAC OTHV200E12WP

Brand: ABB | Manufacturer Part Number: 1SCA162963R1001



Manufacturer	ABB
MPN / Reference	1SCA162963R1001
Catalog number	1SCA162963R1001
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-C6F5B4D1DD
Generated	2026-08-02

Product Overview

Int. Sec. for 800-1000VAC OTHV200E12WP
OTHV200E12WP SWITCH DISCONNECTOR

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	ABB > Manual Switches
--------------	-----------------------

Additional Product Information

Material Compliance
Conflict Minerals Reporting Template (CMRT) 9AKK108467A5658
REACH Declaration 1SCC011021D0201
RoHS Declaration 1SCC011020D0201
RoHS Information Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA 1SCC011025D0201
Popular Downloads
Data Sheet, Technical Information 9AKK108469A0610
Instructions and Manuals 1SCC301031M0220
Mechanical Drawings 1SCC301294F0001
1SCC301293F0001
Environmental
Degree of Protection Front IP00
Pollution Degree 3

Ordering

Minimum Order Quantity 1 piece

Customs Tariff Number 85365080

Country or Territory of Origin Finland

Dimensions

Product Net Width 174.5 mm

Product Net Height 170 mm

Product Net Depth / Length 82.5 mm

Product Net Weight 1.5 kg

Container Information

Package Level 1 Units box 1 piece

Package Level 1 Width 110 mm

Package Level 1 Depth / Length 190 mm

Package Level 1 Height 290 mm

Package Level 1 Gross Weight 1.6 kg

Package Level 1 EAN 6417019929156

TechnicalConventional Free-air Thermal Current (I_{th}) 200 AConventional Thermal Current (I_{the}) 200 A

Degree of Protection Front IP00

Handle Color Black

Handle Length 65 mm

Handle Type Pistol type handle included

Mechanical Durability Nr. Operations 20000

Mounting Type Base mounting

Number of Poles 3P

Operating Mode Front

Pollution Degree 3

Rated Impulse Withstand Voltage (U_{imp}) 12 kVRated Insulation Voltage (U_i) acc. to IEC 60947-1 1000 VRated Operational Current AC-21A (I_e) (800 V AC) 200 A
(1000 V AC) 200 A

Rated Oper...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SCA162963R1001 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.