

INDUSTRIAL COMPONENT DATA

1SCA162969R1001 ABB Int. Sec. for 800-1000VAC OTHV2500E12P

Brand: ABB | Manufacturer Part Number: 1SCA162969R1001



Manufacturer	ABB
MPN / Reference	1SCA162969R1001
Catalog number	1SCA162969R1001
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-13BA5E8825
Generated	2026-07-31

Product Overview

Int. Sec. for 800-1000VAC OTHV2500E12P
OTHV2500E12P SWITCH DISCONNECTOR

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **ABB > Manual Switches**

Additional Product Information

Material Compliance
Conflict Minerals Reporting Template (CMRT) 9AKK108467A5658
REACH Declaration 1SCC011021D0201
RoHS Declaration 1SCC011020D0201
RoHS Information Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA 1SCC011025D0201
Popular Downloads
Data Sheet, Technical Information 9AKK108469A0610
Instructions and Manuals 1SCC301078M0205
Mechanical Drawings 1SCC301522F0001
1SCC301521F0001
OT2500E12.igs
Environmental
Degree of Protection Front IP00

Pollution Degree 3

Ordering

Minimum Order Quantity 1 piece

Customs Tariff Number 85365080

Country or Territory of Origin Finland

Dimensions

Product Net Width 472.5 mm

Product Net Height 376.5 mm

Product Net Depth / Length 145.5 mm

Product Net Weight 25.8 kg

Container Information

Package Level 1 Units box 1 piece

Package Level 1 Width 190 mm

Package Level 1 Depth / Length 407 mm

Package Level 1 Height 619 mm

Package Level 1 Gross Weight 27.7 kg

Package Level 1 EAN 6417019929217

Technical

Conventional Free-air Thermal Current (Ith) 2500 A

Conventional Thermal Current (Ithe) 2500 A

Degree of Protection Front IP00

Handle Color Black

Handle Length 274 mm

Handle Type Pistol type handle included

Mechanical Durability Nr. Operations 6000

Mounting Type Base mounting

Number of Poles 3P

Operating Mode Front

Pollution Degree 3

Rated Impulse Withstand Voltage (Uimp) 12 kV

Rated Insulation Voltage (Ui) acc. to IEC 60947-1 1000 V

Rated Operational Current AC-21B (Ie) (800 V) 2500 A

Rated Ope...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SCA162969R1001 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.