

INDUSTRIAL COMPONENT DATA

1SDA056908R1 ABB E4V3200 PR122/P LSI 4P W MP

Brand: ABB | Manufacturer Part Number: 1SDA056908R1



Manufacturer	ABB
MPN / Reference	1SDA056908R1
Catalog number	056908
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-CFB35B6E9F
Generated	2026-08-02

Product Overview

E4V3200 PR122/P LSI 4P W MP

E4V 3200 PR122/P-LSI In=3200A 4p W MP

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Service Breakers

Additional Product Information

Extended Product Type:E4V3200PR122/P-LSIIn=3200A4pWMP

Product ID:1SDA056908R1

EAN:8015644582487

Catalog Description:E4V 3200 PR122/P-LSI In=3200A 4p W MP

Long Description:SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E4V 3200A FOUR-POLE OVERCURRENT RELEASE PR122/P-LSI R3200 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Ordering

EAN:8015644582487

Minimum Order Quantity:1 piece

Customs Tariff Number:85362090

Dimensions

Product Net Width:684mm

Product Net Height:461mm

Product Net Depth / Length:396.5mm

Product Net Weight:96kg

Container Information

Package Level 1 Units:1 piece

Package Level 1 Width:515 mm

Package Level 1 Height:600 mm

Package Level 1 Depth / Length:920 mm

Package Level 1 Gross Weight:116 kg

Package Level 1 EAN:8015644582487

Environmental

RoHS Status:Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Conflict Minerals Reporting Template (CMRT):Document availability on demand

Environmental Information:9AKK10103A6076

REACH Declaration:9AKK108466A1425

RoHS Information:9AKK108466A1424

Additional Information

Current Type:AC

Electrical Durability:Ue =< 440 V 7000 cycle

Ue = 500 ... 690 V 7000 cycle

10 cycles per hour

Mechanical Durability:15000 cycle

60 cycles per hour

Number of Poles:4

Power Loss:425 W

Product Main Type:SACE Emax

Product Name:Air Circuit Breaker

Product Type:Air Circuit Breaker

Rated Current (In):3200 A

Rated Voltage (Ur):690 V

Rated Impulse Withstand Voltage (Uimp):12 kV

Rated Insulation Voltage (Ui):1000 V

R...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEWSend ABB / 1SDA056908R1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.