

INDUSTRIAL COMPONENT DATA

1SDA058917R1 ABB E6H/E/MS 5000 3P F HR 750VDC

Brand: ABB | Manufacturer Part Number: 1SDA058917R1



Manufacturer	ABB
MPN / Reference	1SDA058917R1
Catalog number	058917
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-E509A6D340
Generated	2026-07-29

Product Overview

E6H/E/MS 5000 3P F HR 750VDC

E6H/E/MS 5000 3p F HR 750V DC new

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Service Breakers

Additional Product Information

ABB EcoSolutions

Material Compliance

REACH Declaration 9AKK108466A1425

RoHS Declaration 9AKK108466A1424

RoHS Information Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Conflict Minerals Reporting Template (CMRT) 9AKK108467A5658

Toxic Substances Control Act - TSCA 9AKK108467A8326

Environmental

Environmental Information 9AKK10103A6076

Ordering

EAN 8015644612702

Minimum Order Quantity 1 piece

Customs Tariff Number 85362090

Dimensions

Product Net Width 782 mm

Product Net Height 418 mm
Product Net Depth / Length 302 mm
Product Net Weight 112 kg
Container Information
Package Level 1 Units box 1 piece
Package Level 1 Width 515 mm
Package Level 1 Height 600 mm
Package Level 1 Depth / Length 1000 mm
Package Level 1 Gross Weight 133 kg
Package Level 1 EAN 8015644612702
Additional Information
Product Main Type SACE Emax
Product Name Switch Disconnecter
Product Type Switch-disconnector
Version F
Technical
Current Type DC
Electrical Durability 3000 cycle
10 cycles per hour
Mechanical Durability 12000 cycle
60 cycles per hour
Number of Poles 3P
Power Loss 415 W
Rated Current (In) 5000 A
Rated Impulse Withstand Voltage (Uimp) 12 kV
Rated Insulation Voltage (Ui) 1000 V
Rated Operational Current (Ie) 5000 A
Rated Operational Voltage 750 V DC
Rated Short-time Withstand Current Low Voltage (Icw) for 1 s 65 kA
Rated Uninterrupted Current (Iu) 5000 A
Rated Voltage (Ur) 750 V
Short-Circuit Performance Level H
Standards IEC
Sub-type E6
Terminal Connection Type Fixed Circuit...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SDA058917R1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.