

INDUSTRIAL COMPONENT DATA

1SDA058922R1 ABB E6H/E/MS 4000 4P W MP 1000VDC

Brand: ABB | Manufacturer Part Number: 1SDA058922R1



Manufacturer	ABB
MPN / Reference	1SDA058922R1
Catalog number	058922
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-C068552F4B
Generated	2026-08-05

Product Overview

E6H/E/MS 4000 4P W MP 1000VDC
E6H/E/f/MS 4000 4p W MP 1000V DC new

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	ABB > Service Breakers
--------------	------------------------

Additional Product Information

ABB EcoSolutions
Material Compliance
REACH Declaration 9AKK108466A1425
RoHS Declaration 9AKK108466A1424
RoHS Information Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Conflict Minerals Reporting Template (CMRT) 9AKK108467A5658
Toxic Substances Control Act - TSCA 9AKK108467A8326
Environmental
Environmental Information 9AKK10103A6076
Ordering
EAN 8015644612757
Minimum Order Quantity 1 piece
Customs Tariff Number 85362090
Dimensions
Product Net Width 1062 mm

Product Net Height 461 mm
Product Net Depth / Length 396.5 mm
Product Net Weight 135 kg
Container Information
Package Level 1 Units box 1 piece
Package Level 1 Width 515 mm
Package Level 1 Height 600 mm
Package Level 1 Depth / Length 1257 mm
Package Level 1 Gross Weight 161 kg
Package Level 1 EAN 8015644612757
Additional Information
Product Main Type SACE Emax
Product Name Switch Disconnecter
Product Type Air Circuit Breaker
Version W
Technical
Current Type DC
Mechanical Durability 12000 cycle
60 cycles per hour
Number of Poles 4 / f
Power Loss 445 W
Rated Current (In) 4000 A
Rated Impulse Withstand Voltage (Uimp) 12 kV
Rated Insulation Voltage (Ui) 1000 V
Rated Operational Current (Ie) 4000 A
Rated Operational Voltage 1000 V DC
Rated Short-time Withstand Current Low Voltage (Icw) for 1 s 65 kA
Rated Uninterrupted Current (Iu) 4000 A
Rated Voltage (Ur) 1000 V
Short-Circuit Performance Level H
Standards IEC
Sub-type E6
Terminal Connection Type Withdrawable Circuit-Breakers
Certificates and Declaratio...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SDA058922R1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.