

INDUSTRIAL COMPONENT DATA

1SDA059047R1 ABB E1B/E MS 1250 3P W MP 750VDC

Brand: ABB | Manufacturer Part Number: 1SDA059047R1



Manufacturer	ABB
MPN / Reference	1SDA059047R1
Catalog number	059047
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-27B6FEFB7A
Generated	2026-08-03

Product Overview

E1B/E MS 1250 3P W MP 750VDC
E1B/E MS 1250 3p 750V DC W MP new

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	ABB > Service Breakers
--------------	------------------------

Additional Product Information

ABB EcoSolutions
Material Compliance
REACH Declaration 9AKK108466A1425
RoHS Declaration 9AKK108466A1424
RoHS Information Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA 9AKK108467A8326
Environmental
Environmental Information 9AKK10103A6076
Ordering
EAN 8015644614065
Minimum Order Quantity 1 piece
Customs Tariff Number 85362090
Dimensions
Product Net Width 324 mm
Product Net Height 461 mm

Product Net Depth / Length 396.5 mm

Product Net Weight 44 kg

Container Information

Package Level 1 Units box 1 piece

Package Level 1 Width 515 mm

Package Level 1 Height 600 mm

Package Level 1 Depth / Length 515 mm

Package Level 1 Gross Weight 55 kg

Package Level 1 EAN 8015644614065

Additional Information

Product Main Type SACE Emax

Product Name Switch Disconnecter

Product Type Air Circuit Breaker

Version W

Technical

Current Type DC

Electrical Durability 10000 cycle

30 cycles per hour

Mechanical Durability 25000 cycle

60 cycles per hour

Number of Poles 3P

Power Loss 230 W

Rated Current (In) 1250 A

Rated Impulse Withstand Voltage (Uimp) 12 kV

Rated Insulation Voltage (Ui) 1000 V

Rated Operational Current (Ie) 1250 A

Rated Operational Voltage 750 V DC

Rated Short-time Withstand Current Low Voltage (Icw) for 1 s 20 kA

Rated Uninterrupted Current (Iu) 1250 A

Rated Voltage (Ur) 750 V

Short-Circuit Performance Level B

Standards IEC

Sub-type E1

Terminal Connection Type Withdrawable Circuit-Breakers

Certificates and Declarations

Data Sheet, T...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SDA059047R1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.