

INDUSTRIAL COMPONENT DATA

1SDA064589R1 ABB E2N1600 PR122/DC 4P F VR

Brand: ABB | Manufacturer Part Number: 1SDA064589R1



Manufacturer	ABB
MPN / Reference	1SDA064589R1
Catalog number	064589
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-02CD31AE45
Generated	2026-08-02

Product Overview

E2N1600 PR122/DC 4P F VR

E2N 1600 PR122/DC In=1600A 4p F VR

[More details](#)
STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **ABB > Service Breakers**

Additional Product Information

ABB EcoSolutions

Material Compliance

REACH Declaration 9AKK108466A1425

RoHS Declaration 9AKK108466A1424

RoHS Information Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Toxic Substances Control Act - TSCA 9AKK108467A8326

Environmental

Environmental Information 9AKK10103A6076

Ordering

EAN 8015644674823

Minimum Order Quantity 1 piece

Customs Tariff Number 85362090

Dimensions

Product Net Width 386 mm

Product Net Height 418 mm
Product Net Depth / Length 302 mm
Product Net Weight 56 kg
Container Information
Package Level 1 Units box 1 piece
Package Level 1 Width 515 mm
Package Level 1 Height 600 mm
Package Level 1 Depth / Length 615 mm
Package Level 1 EAN 8015644609139
Additional Information
Product Main Type SACE Emax
Product Name Air Circuit Breaker
Product Type Air Circuit Breaker
Version F
Technical
Current Type DC
Electrical Durability $U_e = 1000 \text{ V}$ 10000 cycle
Mechanical Durability 25000 cycle
60 cycles per hour
Number of Poles 4P
Power Loss 174 W
Rated Current (I_n) 1600 A
Rated Impulse Withstand Voltage (U_{imp}) 12 kV
Rated Insulation Voltage (U_i) 1000 V
Rated Operational Current (I_e) 1600 A
Rated Operational Voltage 1000 V DC
Rated Service Short-Circuit Breaking Capacity (I_{cs}) (750 V DC) 40 kA
(1000 V DC) 25 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}) (750 V DC) 40 kA
(1000 V DC) 25 kA
Rated Uninterrupted Current (I_u) 1600 A
Rated Voltage (U_r) 1000 V
Release PR122/DC
Release Type EL
Short-Circuit Performance Level N
Standards IEC
Sub-type E2...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SDA064589R1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.