

INDUSTRIAL COMPONENT DATA

1SDA064704R1 ABB E3H2000 PR123/DC 4P F VR

Brand: ABB | Manufacturer Part Number: 1SDA064704R1



Manufacturer	ABB
MPN / Reference	1SDA064704R1
Catalog number	064704
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-F951D934F6
Generated	2026-08-03

Product Overview

E3H2000 PR123/DC 4P F VR

E3H 2000 PR123/DC In=2000A 4p F VR

[More details](#)
STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **ABB > Service Breakers**

Additional Product Information

ABB EcoSolutions

Material Compliance

REACH Declaration 9AKK108466A1425

RoHS Declaration 9AKK108466A1424

RoHS Information Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Toxic Substances Control Act - TSCA 9AKK108467A8326

Environmental

Environmental Information 9AKK10103A6076

Ordering

EAN 8015644675974

Minimum Order Quantity 1 piece

Customs Tariff Number 85362090

Dimensions

Product Net Width 530 mm

Product Net Height 418 mm

Product Net Depth / Length 302 mm

Product Net Weight 76 kg

Container Information

Package Level 1 Units box 1 piece

Package Level 1 Width 515 mm

Package Level 1 Height 600 mm

Package Level 1 Depth / Length 785 mm

Package Level 1 Gross Weight 90 kg

Package Level 1 EAN 8015644609139

Additional Information

Product Main Type SACE Emax

Product Name Air Circuit Breaker

Product Type Air Circuit Breaker

Version F

Technical

Current Type DC

Electrical Durability $U_e = 1000\text{ V}$ 9000 cycle

Mechanical Durability 20000 cycle

60 cycles per hour

Number of Poles 4P

Power Loss 288 W

Rated Current (I_n) 2000 A

Rated Impulse Withstand Voltage (U_{imp}) 12 kV

Rated Insulation Voltage (U_i) 1000 V

Rated Operational Current (I_e) 2000 A

Rated Operational Voltage 1000 V DC

Rated Service Short-Circuit Breaking Capacity (I_{cs}) (750 V DC) 50 kA
(1000 V DC) 40 kA

Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}) (750 V DC) 50 kA
(1000 V DC) 40 kA

Rated Uninterrupted Current (I_u) 2000 A

Rated Voltage (U_r) 1000 V

Release PR123/DC

Release Type EL

Short-Circuit Performance...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SDA064704R1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.