

INDUSTRIAL COMPONENT DATA

1SDA064740R1 ABB E4S/f 2000 PR123/DC 4P W MP

Brand: ABB | Manufacturer Part Number: 1SDA064740R1



Manufacturer	ABB
MPN / Reference	1SDA064740R1
Catalog number	064740
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-CFA4D28916
Generated	2026-08-01

Product Overview

E4S/f 2000 PR123/DC 4P W MP

SACE EMAX MOVING PART FOR CIRCUIT-BREAKER E4S/f 2000A FOUR-POLE OVERCURRENT RELEASE
PR123/DC R2000 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Service Breakers

Additional Product Information

b'
General Information
Extended Product Type:E4S/f2000PR123/DCIn=2000A4pWMPProduct ID:1SDA064740R1EAN:8015644676339Catalog
Description:E4S/f 2000 PR123/DC In=2000A 4p W MPLong Description:SACE EMAX MOVING PART FOR
CIRCUIT-BREAKER E4S/f 2000A FOUR-POLE OVERCURRENT RELEASE PR123/DC R2000 FITTED WITH: 4
AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED\nOrdering
EAN:8015644676339Minimum Order Quantity:1 pieceCustoms Tariff Number:85362090Dimensions
Product Net Width:774 mmProduct Net Height:461 mmProduct Net Depth / Length:396.5 mmProduct Net Weight:96
kgContainer Information
Package Level 1 Units:1 piecePackage Level 1 Width:515 mmPackage Level 1 Height:600 mmPackage Level 1 Depth /
Length:1000 mmPackage Level 1 EAN:8015644609139Additional Information
Current Type:DCElectrical Durability:Ue = 1000 V 7000 cycleMechanical Durability:15000 cycle
60 cycles per hourNumber of Poles:4 / fPower Loss:280 WProduct Main Type:SACE EmaxProduct Name:Air Circuit
BreakerProduct Type:Air Circuit BreakerRated Current (In):2000 ARated Voltage (Ur):1000 VRated Impulse Withstand

Voltage (Uimp):12 kVRated Insulation Voltage (Ui):1000 VRated Operational Current (Ie):2000 ARated Operational Voltage:1000 V DCRated Service Short-Circuit Breaking Capacity (Ics):(750 V DC) 65 kA
(1000 V DC) 50 kARated Ultimate Short-Circuit Breaking Capacity (Icu):(750 V DC) 65 kA
(1000 V DC) 50 kARated Uninterrupted Current (Iu):2000 ARelease:PR123/DCRelease Type:ELShort-Circuit Performance Level:SSStandards:IECSub...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SDA064740R1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.