

INDUSTRIAL COMPONENT DATA

1SDA068511R1 ABB XT4H160 Ekip LS/I R40 3P F F

Brand: ABB | Manufacturer Part Number: 1SDA068511R1



Manufacturer	ABB
MPN / Reference	1SDA068511R1
Catalog number	068511
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-623E3AB6D2
Generated	2026-08-03

Product Overview

XT4H160 Ekip LS/I R40 3P F F

C.BREAKER TMAX XT4H 160 FIXED THREE-POLE WITH FRONT TERMINALS AND SOLID-STATE RELEASE IN AC EKIP-LS/I R 40 A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Molded Case Circuit Breakers <= 250 A Xtmax

Additional Product Information

b'

General Information

Extended Product Type:XT4H 160 Ekip LS/I In=40A 3p F FProduct ID:1SDA068511R1EAN:8015644024178Catalog Description:XT4H 160 Ekip LS/I In=40A 3p F FLong Description:C.BREAKER TMAX XT4H 160 FIXED THREE-POLE WITH FRONT TERMINALS AND SOLID-STATE RELEASE IN AC EKIP-LS/I R 40 A\nOrdering EAN:8015644024178Minimum Order Quantity:1 pieceCustoms Tariff Number:85362090Dimensions Product Net Width:105 mmProduct Net Height:160 mmProduct Net Depth / Length:82.5 mmProduct Net Weight:2.05 kgContainer Information

Package Level 1 Units:1 piecePackage Level 1 Width:145 mmPackage Level 1 Height:210 mmPackage Level 1 Depth / Length:168 mmPackage Level 1 Gross Weight:2.5 kgPackage Level 1 EAN:8015644024178Environmental RoHS Status:Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019Additional Information Circuit Breaker Type to be Associated:Power DistributionCurrent Type:ACElectrical Durability:120 cycles per hour 8000 cycleMechanical Durability:Nr. Operations 240 cycles per hour Nr. Operations 25000 cycleNumber of Poles:3Opening Time:CB with SOR 15 ms

CB with UVR 15 msOrder Multiple:1 pieceProduct Main Type:SACE Tmax XTProduct Name:Moulded Case Circuit BreakerProduct Type:CBRated Current (In):40 ARated Frequency (f):50 / 60 HzRated Voltage (Ur):690 VRated Impulse Withstand Voltage (Uimp):8 kVRated Insulation Voltage (Ui):1000 VRated Operational Voltage:690 V ACRated Service Short-Circuit Breaking Capacity (Ics):(220 V AC) 100 kA
(230 V AC) 100 kA
(240 V A...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SDA068511R1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.