

INDUSTRIAL COMPONENT DATA

1SDA074367R1 ABB E2.2MTP 2500 4P W MP GROUND SUP.

Brand: ABB | Manufacturer Part Number: 1SDA074367R1



Manufacturer	ABB
MPN / Reference	1SDA074367R1
Catalog number	074367
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-C459E879CB
Generated	2026-08-01

Product Overview

E2.2MTP 2500 4P W MP GROUND SUP.

E2.2MTP 2500 MP 4p Earth UP

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Rack "Megamax-Emax"

Additional Product Information

ABB EcoSolutions

Material Compliance

REACH Declaration 9AKK108466A1425

RoHS Declaration 9AKK108466A1424

RoHS Information Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Conflict Minerals Reporting Template (CMRT) 9AKK108467A5658

Toxic Substances Control Act - TSCA 9AKK108467A8326

Environmental

Environmental Information 9AKK108467A6707

Ordering

EAN 8015644783006

Minimum Order Quantity 1 piece

Customs Tariff Number 85362090

Dimensions

Product Net Width 317 mm

Product Net Height 425 mm
Product Net Depth / Length 383 mm
Product Net Weight 64 kg
Container Information
Package Level 1 Units box 1 piece
Package Level 1 Width 515 mm
Package Level 1 Height 610 mm
Package Level 1 Depth / Length 515 mm
Package Level 1 Gross Weight 77 kg
Package Level 1 EAN 8015644783006
Additional Information
Product Main Type SACE Emax 2
Product Name Derived Version
Product Type Derived version - Earthing switch with making capacity MTP
Version W
Technical
Connecting Capacity 1800 mm²
Current Type AC
Electrical Durability 2000 cycle
Mechanical Durability 20000 cycle
60 cycles per hour
Neutral Pole Current ([%I_u]) 100 %
Number of Poles 4P
Rated Current (I_n) 2500 A
Rated Impulse Withstand Voltage (U_{imp}) 12 kV
Rated Insulation Voltage (U_i) AC 1000 V
Rated Operational Voltage 690 V AC
Rated Short-time Withstand Current Low Voltage (I_{cw}) for 1 s 30 kA
Rated Uninterrupted Current (I_u) 2500 A
Rated Voltage (U_r) 690 V
Recommended Screw Driver M12
Standards IEC
Sub-type E2.2
Certificates....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SDA074367R1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.