

## INDUSTRIAL COMPONENT DATA

## 1SDA100041R1 ABB XT2S 160 Ekip Dip LIG In 25A 3p F F

Brand: ABB | Manufacturer Part Number: 1SDA100041R1



|                 |                                                                   |
|-----------------|-------------------------------------------------------------------|
| Manufacturer    | ABB                                                               |
| MPN / Reference | 1SDA100041R1                                                      |
| Catalog number  | 100041                                                            |
| Category        | Power circuit-breaker for trafo/generator/installation protection |
| Minimum order   | 1 Pcs                                                             |
| Document ID     | EO-FD8FBBD7C6                                                     |
| Generated       | 2026-08-01                                                        |

## Product Overview

XT2S 160 Ekip Dip LIG In=25A 3p F F

C.BREAKER TMAX XT2S 160 FIXED THREE-POLE WITH FRONT TERMINALS AND SOLID-STATE RELEASE IN AC EKIP DIP LIG R 25 A

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification &amp; Catalog Path

Catalog path ABB &gt; Molded Case Circuit Breakers &lt;= 250 A Tmax

## Additional Product Information

b'

General Information

Extended Product Type:XT2S 160 Ekip Dip LIG In=25A 3p F FProduct ID:1SDA100041R1EAN:8056221000956Catalog Description:XT2S 160 Ekip Dip LIG In=25A 3p F FLong Description:C.BREAKER TMAX XT2S 160 FIXED THREE-POLE WITH FRONT TERMINALS AND SOLID-STATE RELEASE IN AC EKIP DIP LIG R 25 A\nOrdering EAN:8056221000956Minimum Order Quantity:1 pieceCustoms Tariff Number:85362090Dimensions Product Net Width:90 mmProduct Net Height:130 mmProduct Net Depth / Length:82.5 mmProduct Net Weight:1.12 kgContainer Information

Package Level 1 Units:1 piecePackage Level 1 Width:130 mmPackage Level 1 Height:208 mmPackage Level 1 Depth / Length:145 mmPackage Level 1 Gross Weight:1.22 kgPackage Level 1 EAN:8056221000956Additional Information

Circuit Breaker Type to be Associated:Power DistributionCurrent Type:ACElectrical Durability:120 cycles per hour 8000 cycleMechanical Durability:240 cycles per hour

25000 cycleNumber of Poles:3Order Multiple:1 piecePower Loss:at Rated Operating Conditions per Pole 0.8 WProduct Main Type:SACE Tmax XTProduct Name:Moulded Case Circuit BreakerProduct Type:CBRated Current (In):25 ARated

Impulse Withstand Voltage (Uimp):8 kVRated Insulation Voltage (Ui):1000 VRated Operational Voltage:690 V ACRated  
Service Short-Circuit Breaking Capacity (Ics):(220 V AC) 85 kA  
(230 V AC) 85 kA  
(240 V AC) 85 kA  
(380 V AC) 50 kA  
(415 V AC) 50 kA  
(440 V AC) 50 kA  
(500 V AC) 36 kA  
(525 V AC) 25 kA  
(690 V AC) 12 kARated Ultimate Short-Circuit Breaking Capacity (Icu):(22...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SDA100041R1 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.