

INDUSTRIAL COMPONENT DATA

1SDA100207R1 ABB XT4S 160 Ekip Dip LSIG In 63A 3p F F

Brand: ABB | Manufacturer Part Number: 1SDA100207R1



Manufacturer	ABB
MPN / Reference	1SDA100207R1
Catalog number	1SDA100207R1
Category	Shunt release (for power circuit breaker)
Minimum order	1 Pcs
Document ID	EO-B7D16D6327
Generated	2026-08-03

Product Overview

XT4S 160 Ekip Dip LSIG In=63A 3p F F

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Molded Case Circuit Breakers <= 250 A Xtmax

Additional Product Information

ABB EcoSolutions

Environmental Product Declaration - EPD 9AKK108469A1858

Recyclability Rate of the Product acc. to EN45555 Design for Closing Resource Loops - Standard EN45555 - 56.30 %

Material Compliance

REACH Declaration 9AKK108466A1425

RoHS Declaration 9AKK108466A1424

RoHS Information Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Conflict Minerals Reporting Template (CMRT) 9AKK108467A5658

Toxic Substances Control Act - TSCA 9AKK108467A8326

Ordering

EAN 8056221002615

Minimum Order Quantity 1 piece

Customs Tariff Number 85362090

Dimensions

Product Net Width 105 mm

Product Net Height 160 mm

Product Net Depth / Length 82.5 mm

Product Net Weight 2.5 kg

Container Information

Package Level 1 Units box 1 piece

Package Level 1 Width 145 mm

Package Level 1 Height 210 mm

Package Level 1 Depth / Length 168 mm

Package Level 1 Gross Weight 2.5 kg

Package Level 1 EAN 8056221002615

Additional Information

Circuit Breaker Type to be Associated Power Distribution

Product Main Type SACE Tmax XT

Product Name Moulded Case Circuit Breaker

Product Type Automatic Circuit Breaker

Version F

CAD Dimensional Drawing 1SDH002230A1003

Technical

Current Type AC

Electrical Durability 120 cycles per hour

8000 cycle

Mechanical Durability 240 cycles per hour

25000 cycle

Number of Poles 3P

Opening Time CB with SOR 30 ms

CB with UVR 30 ms

Power Loss at Rated Operating Conditions per Pole 1.40 W

Rated Current (In) 63 A

Rated Frequency (f) 50/60 Hz

Rated Impulse Withstand Voltage (Uimp)...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SDA100207R1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.