

INDUSTRIAL COMPONENT DATA

1SDA100899R1 ABB XT7H 1000 Ekip Dip LSIG In 1000A 3p F F

Brand: ABB | Manufacturer Part Number: 1SDA100899R1



Manufacturer	ABB
MPN / Reference	1SDA100899R1
Catalog number	100899
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-40225F701D
Generated	2026-08-01

Product Overview

XT7H 1000 Ekip Dip LSIG In=1000A 3p F F

C.BREAKER TMAX XT7H 1000 FIXED THREE-POLE WITH FRONT TERMINALS AND LEVER OPERATING MECHANISM AND SOLID-STATE RELEASE IN AC EKIP DIP LSIG R 1000

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Molded case "Isomax-Tmax"

Additional Product Information

b'

General Information

Extended Product Type:XT7H 1000 Ekip Dip LSIG In=1000A 3p F FProduct ID:1SDA100899R1EAN:8056221009539Catalog Description:XT7H 1000 Ekip Dip LSIG In=1000A 3p F FLong Description:C.BREAKER TMAX XT7H 1000 FIXED THREE-POLE WITH FRONT TERMINALS AND LEVER OPERATING MECHANISM AND SOLID-STATE RELEASE IN AC EKIP DIP LSIG R 1000\nOrdering EAN:8056221009539Minimum Order Quantity:1 pieceCustoms Tariff Number:85362090Dimensions Product Net Width:210 mmProduct Net Height:268 mmProduct Net Depth / Length:166 mmProduct Net Weight:9.7 kgContainer Information

Package Level 1 Units:1 piecePackage Level 1 Width:280 mmPackage Level 1 Height:350 mmPackage Level 1 Depth / Length:360 mmPackage Level 1 Gross Weight:11.2 kgPackage Level 1 EAN:8056221009539Additional Information

Circuit Breaker Type to be Associated:Power DistributionCurrent Type:ACElectrical Durability:120 cycles per hour 3000 cycleMechanical Durability:240 cycles per hour 10000 cycleNumber of Poles:3Order Multiple:1 piecePower Loss:at Rated Operating Conditions per Pole 37 WProduct

Main Type:SACE Tmax XTP
Product Name:Moulded Case Circuit Breaker
Product Type:CB
Rated Current (In):1000 A
Rated Impulse Withstand Voltage (Uimp):8 kV
Rated Insulation Voltage (Ui):1000 V
Rated Operational Voltage:690 V AC
Rated Service Short-Circuit Breaking Capacity (Ics):(220 V AC) 100 kA
(230 V AC) 100 kA
(240 V AC) 100 kA
(380 V AC) 70 kA
(415 V AC) 70 kA
(440 V AC) 65 kA
(500 V AC) 50 kA
(525 V AC) 50 kA
(690 V AC) 42 kA
Rated Short-t...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SDA100899R1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.