

## INDUSTRIAL COMPONENT DATA

# 1SDA100962R1 ABB XT7L 800 Ekip Dip LSIG In 800A 3p F F

Brand: ABB | Manufacturer Part Number: 1SDA100962R1



|                 |                                                                   |
|-----------------|-------------------------------------------------------------------|
| Manufacturer    | ABB                                                               |
| MPN / Reference | 1SDA100962R1                                                      |
| Catalog number  | 100962                                                            |
| Category        | Power circuit-breaker for trafo/generator/installation protection |
| Minimum order   | 1 Pcs                                                             |
| Document ID     | EO-37FB403231                                                     |
| Generated       | 2026-08-03                                                        |

## Product Overview

XT7L 800 Ekip Dip LSIG In=800A 3p F F

C.BREAKER TMAX XT7L 800 FIXED THREE-POLE WITH FRONT TERMINALS AND LEVER OPERATING MECHANISM AND SOLID-STATE RELEASE IN AC EKIP DIP LSIG R 800

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path ABB &gt; Molded case "Isomax-Tmax"

## Additional Product Information

b'

General Information

Extended Product Type:XT7L 800 Ekip Dip LSIG In=800A 3p F FProduct ID:1SDA100962R1EAN:8056221010160Catalog Description:XT7L 800 Ekip Dip LSIG In=800A 3p F FLong Description:C.BREAKER TMAX XT7L 800 FIXED THREE-POLE WITH FRONT TERMINALS AND LEVER OPERATING MECHANISM AND SOLID-STATE RELEASE IN AC EKIP DIP LSIG R 800\nOrdering

EAN:8056221010160Minimum Order Quantity:1 pieceCustoms Tariff Number:85362090Dimensions

Product Net Width:210 mmProduct Net Height:268 mmProduct Net Depth / Length:166 mmProduct Net Weight:9.7 kgContainer Information

Package Level 1 Units:1 piecePackage Level 1 Width:280 mmPackage Level 1 Height:350 mmPackage Level 1 Depth / Length:360 mmPackage Level 1 Gross Weight:11.2 kgPackage Level 1 EAN:8056221010160Additional Information

Circuit Breaker Type to be Associated:Power DistributionCurrent Type:ACElectrical Durability:120 cycles per hour 3000 cycleMechanical Durability:240 cycles per hour 10000 cycleNumber of Poles:3Order Multiple:1 piecePower Loss:at Rated Operating Conditions per Pole 24 WProduct

Main Type:SACE Tmax XTProduct Name:Moulded Case Circuit BreakerProduct Type:CBRated Current (In):800 ARated Impulse Withstand Voltage (Uimp):8 kVRated Insulation Voltage (Ui):1000 VRated Operational Voltage:690 V ACRated Service Short-Circuit Breaking Capacity (Ics):(220 V AC) 200 kA  
(230 V AC) 200 kA  
(240 V AC) 200 kA  
(380 V AC) 120 kA  
(415 V AC) 120 kA  
(440 V AC) 100 kA  
(500 V AC) 85 kA  
(525 V AC) 65 kA  
(690 V AC) 50 kARated Short-time....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SDA100962R1 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.