

INDUSTRIAL COMPONENT DATA

1SDA101264R1 ABB XT7L 1250 Ekip G Dip LS/I In1250A 4p F F

Brand: ABB | Manufacturer Part Number: 1SDA101264R1



Manufacturer	ABB
MPN / Reference	1SDA101264R1
Catalog number	101264
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-0603099C31
Generated	2026-08-04

Product Overview

XT7L 1250 Ekip G Dip LS/I In1250A 4p F F

C.BREAKER TMAX XT7L 1250 FIXED FOUR-POLE WITH FRONT TERMINALS AND LEVER OPERATING MECHANISM AND SOLID-STATE RELEASE IN AC EKIP G DIP LS/I R 1250

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Molded case "Isomax-Tmax"

Additional Product Information

b'

General Information

Extended Product Type:XT7L 1250 Ekip G Dip LS/I In1250A 4p F FProduct ID:1SDA101264R1EAN:8056221010825Catalog Description:XT7L 1250 Ekip G Dip LS/I In1250A 4p F FLong Description:C.BREAKER TMAX XT7L 1250 FIXED FOUR-POLE WITH FRONT TERMINALS AND LEVER OPERATING MECHANISM AND SOLID-STATE RELEASE IN AC EKIP G DIP LS/I R 1250\nOrdering EAN:8056221010825Minimum Order Quantity:1 pieceCustoms Tariff Number:85362090Dimensions Product Net Width:280 mmProduct Net Height:268 mmProduct Net Depth / Length:166 mmProduct Net Weight:12.5 kgContainer Information Package Level 1 Units:1 piecePackage Level 1 Width:360 mmPackage Level 1 Height:350 mmPackage Level 1 Depth / Length:360 mmPackage Level 1 Gross Weight:14 kgPackage Level 1 EAN:8056221010825Additional Information Circuit Breaker Type to be Associated:Generator ProtectionCurrent Type:ACElectrical Durability:120 cycles per hour 3000 cycleMechanical Durability:240 cycles per hour

10000 cycle
Number of Poles:4
Order Multiple:1 piece
Power Loss:at Rated Operating Conditions per Pole 57 W
Product Main Type:SACE Tmax XTP
Product Name:Moulded Case Circuit Breaker
Product Type:CB
Rated Current (In):1250 A
Rated Impulse Withstand Voltage (Uimp):8 kV
Rated Insulation Voltage (Ui):1000 V
Rated Operational Voltage:690 V AC
Rated Service Short-Circuit Breaking Capacity (Ics):
(220 V AC) 200 kA
(230 V AC) 200 kA
(240 V AC) 200 kA
(380 V AC) 120 kA
(415 V AC) 120 kA
(440 V AC) 100 kA
(500 V AC) 85 kA
(525 V AC) 65 kA
(690 V AC) 50 kA
Rated....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SDA101264R1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.