

INDUSTRIAL COMPONENT DATA

1SDA104342R1 ABB E2.2S/E9 2500 Ekip Dip LSI 4p FHR

Brand: ABB | Manufacturer Part Number: 1SDA104342R1



Manufacturer	ABB
MPN / Reference	1SDA104342R1
Catalog number	104342
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-20F89F3B4D
Generated	2026-07-29

Product Overview

E2.2S/E9 2500 Ekip Dip LSI 4p FHR

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Rack "Megamax-Emax"

Additional Product Information

ABB EcoSolutions

ABB EcoSolutions Yes

ABB Site Meeting Group Waste To Landfill Target UL 2799 Zero Waste To Landfill Validation available

End Of Life Disassembling Instructions 9AKK108468A2361

Environmental Product Declaration - EPD 9AKK108471A0821

Material Compliance

REACH Declaration 9AKK108466A1425

RoHS Declaration 9AKK108466A1424

RoHS Information Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Conflict Minerals Reporting Template (CMRT) 9AKK108467A5658

Toxic Substances Control Act - TSCA 9AKK108467A8326

SCIP 5db9272f-d385-4a4a-a0e6-73274e7613b2 Italy

Environmental

Environmental Information 9AKK108467A6707

Ordering

Order Code US and Canada 9BSUELBB000A000000XX

EAN 8015644064228

Minimum Order Quantity 1 piece

Customs Tariff Number 85362090

Dimensions

Product Net Width 366 mm

Product Net Height 371 mm

Product Net Depth / Length 270 mm

Product Net Weight 53 kg

Container Information

Package Level 1 Units box 1 piece

Package Level 1 Width 515 mm

Package Level 1 Height 610 mm

Package Level 1 Depth / Length 515 mm

Package Level 1 Gross Weight 60 kg

Package Level 1 EAN 8015644064228

Additional Information

Product Main Type SACE Emax 2

Product Name Air Circuit Breaker

Product Type Air Circuit Breaker

Version F

Technical

Current Type AC

Electrical Durability $U_e = 900\text{ V}$ 2000 cycle

30 cycles per hour

Mechanical Durability 25000 cycle

60 cycles per hour

Number of Poles 4P

Power Loss 267 W

Rated Current (I_n) 2500 A

Rated Impulse Withstand Voltage (U_{imp}) acc. to I...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SDA104342R1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.