

INDUSTRIAL COMPONENT DATA

1SDA104534R1 ABB E4.2H/E9 4000 Ekip Touch LSIG 4p WMP

Brand: ABB | Manufacturer Part Number: 1SDA104534R1



Manufacturer	ABB
MPN / Reference	1SDA104534R1
Catalog number	104534
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-60D7BB6AF8
Generated	2026-07-29

Product Overview

E4.2H/E9 4000 Ekip Touch LSIG 4p WMP

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Rack "Megamax-Emax"

Additional Product Information

ABB EcoSolutions
ABB EcoSolutions Yes
ABB Site Meeting Group Waste To Landfill Target UL 2799 Zero Waste To Landfill Validation available
End Of Life Disassembling Instructions 9AKK108468A2363
Environmental Product Declaration - EPD 9AKK108471A0821
Extended Product Lifetime Lifetime Extension Services are Offered
Material Compliance
REACH Declaration 9AKK108466A1425
RoHS Declaration 9AKK108466A1424
RoHS Information Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Conflict Minerals Reporting Template (CMRT) 9AKK108467A5658
Toxic Substances Control Act - TSCA 9AKK108467A8326
Environmental
Environmental Information 9AKK108467A6707
Ordering
Order Code US and Canada 9CHWERA000A000000XX

EAN 8056221026536

Minimum Order Quantity 1 piece

Customs Tariff Number 85362090

Dimensions

Product Net Width 551 mm

Product Net Height 425 mm

Product Net Depth / Length 383 mm

Product Net Weight 74 kg

Container Information

Package Level 1 Units box 1 piece

Package Level 1 Width 515 mm

Package Level 1 Height 610 mm

Package Level 1 Depth / Length 615 mm

Package Level 1 Gross Weight 77 kg

Package Level 1 EAN 8056221026536

Additional Information

Product Main Type SACE Emax 2

Product Name Air Circuit Breaker

Product Type Air Circuit Breaker

Version W

Technical

Current Type AC

Electrical Durability $U_e = 900\text{ V}$ 1000 cycle

10 cycles per hour

Mechanical Durability 20000 cycle

60 cycles per hour

Number of Poles 4P

Power Loss 900 W

Rated Current (I_n) 4000 A

Rated Impulse Withstand Voltag...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SDA104534R1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.