

INDUSTRIAL COMPONENT DATA

1SDA115927R1 ABB E2.2H/E10 2500 Ekip Dip LSI 3p WMP

Brand: ABB | Manufacturer Part Number: 1SDA115927R1



Manufacturer	ABB
MPN / Reference	1SDA115927R1
Catalog number	115927
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-2D2E100D23
Generated	2026-07-31

Product Overview

E2.2H/E10 2500 Ekip Dip LSI 3p WMP

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Rack "Megamax-Emax"

Additional Product Information

ABB EcoSolutions
 ABB EcoSolutions Yes
 ABB Site Meeting Group Waste To Landfill Target UL 2799 Zero Waste To Landfill Validation available
 End Of Life Disassembling Instructions 9AKK108468A2361
 Environmental Product Declaration - EPD 9AKK108471A0821
 Extended Product Lifetime Lifetime Extension Services are Offered
 Material Compliance
 REACH Declaration 9AKK108466A1425
 RoHS Declaration 9AKK108466A1424
 RoHS Information Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
 Conflict Minerals Reporting Template (CMRT) 9AKK108467A5658
 Toxic Substances Control Act - TSCA 9AKK108467A8326
 Environmental
 Environmental Information 9AKK108467A6707
 Ordering
 EAN 8056221079976

Minimum Order Quantity 1 piece
Customs Tariff Number 85362090
Dimensions
Product Net Width 317 mm
Product Net Height 425 mm
Product Net Depth / Length 383 mm
Product Net Weight 48 kg
Container Information
Package Level 1 Units box 1 piece
Package Level 1 Width 515 mm
Package Level 1 Height 610 mm
Package Level 1 Depth / Length 515 mm
Package Level 1 Gross Weight 53 kg
Package Level 1 EAN 8056221079976
Additional Information
Product Main Type SACE Emax 2
Product Name Air Circuit Breaker
Product Type Air Circuit Breaker
Version W
Technical
Current Type AC
Electrical Durability $U_e = 1000 \text{ V AC } 500 \text{ cycle}$
30 cycles per hour
Mechanical Durability 20000 cycle
60 cycles per hour
Number of Poles 3P
Power Loss 550 W
Rated Current (I_n) 2500 A
Rated Insulation Voltage (U_i) 1000 V
Rated Operational Voltage 1000 V AC....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SDA115927R1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.