

**INDUSTRIAL COMPONENT DATA**

# 1SFA187055R1300 ABB FASTON DIRECT LAMP BLOCK

Brand: ABB | Manufacturer Part Number: 1SFA187055R1300



|                 |                                               |
|-----------------|-----------------------------------------------|
| Manufacturer    | ABB                                           |
| MPN / Reference | 1SFA187055R1300                               |
| Catalog number  | 187055                                        |
| Category        | Lamp holder block for control circuit devices |
| Minimum order   | 1 Pcs                                         |
| Document ID     | EO-8E94A4291F                                 |
| Generated       | 2026-08-02                                    |

## Product Overview

FASTON DIRECT LAMP BLOCK  
P9PDNF0 Lamp Block

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                             |
|--------------|-----------------------------|
| Catalog path | ABB > Command and signaling |
|--------------|-----------------------------|

## Additional Product Information

**Ordering**

Minimum Order Quantity 10 piece  
Customs Tariff Number 8536619090

**Popular Downloads**

Data Sheet, Technical Information 1SFC151007C02\_\_  
Instructions and Manuals 1SFC151011M0201

**Dimensions**

Product Net Width 9.3 mm  
Product Net Height 36.3 mm  
Product Net Depth / Length 39.4 mm  
Product Net Weight 0.013 kg

**Technical**

Ambient Air Temperature Operation -30 ... 70 °C  
Storage -40 ... +70 °C  
Color Brown

Illumination Illuminated

Lamp Type Lamp block for Ba9s socket for max 2W 380 V AC/DC LED

Mounting Type Front mounting

Rated Frequency (f) 50 / 60 Hz

Rated Operational Voltage Maximum 380 V

Connecting Capacity Flexible with Ferrule 1 x 0.75...2.5 mm<sup>2</sup>

Flexible with Ferrule 2 x 0.75...2.5 mm<sup>2</sup>

Flexible with Insulated Ferrule 1 x 0.75...2.5 mm<sup>2</sup>

Flexible with Insulated Ferrule 2 x 0.75...2.5 mm<sup>2</sup>

Flexible 1 x 0.75 ... 2.5 mm<sup>2</sup>

Flexible 2 x 0.75 ... 2.5 mm<sup>2</sup>

Solid 1 x 0.75...2.5 mm<sup>2</sup>

Solid 2 x 0.75...2.5 mm<sup>2</sup>

Connection Type Faston

Terminal Type Faston

Tightening Torque 0.9 N·m

Wire Stripping Length 8 mm

Technical UL/CSA

Connecting Capacity UL/CSA 1x 18...14 AWG

2x 18...14 AWG

Environmental

Degree of Protection Terminals IP20

Material Compliance

Conflict Minerals Reporting Template (CMRT) 9AKK108467A5658

REACH Declaration 2CMT2022-006479

RoHS Declaration 2CMT2022-006498

RoHS Information Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Toxic Substances Control Act - TSCA 2CMT2023-006523

WEEE B2C / B2B Business To Business

WEEE Category 5. Small Equipment (No External Dime...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SFA187055R1300 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.