

**INDUSTRIAL COMPONENT DATA**

# 1SFA197014R1073 ABB Led Block P9PLNVNG

Brand: ABB | Manufacturer Part Number: 1SFA197014R1073



|                 |                                               |
|-----------------|-----------------------------------------------|
| Manufacturer    | ABB                                           |
| MPN / Reference | 1SFA197014R1073                               |
| Catalog number  | 197014                                        |
| Category        | Lamp holder block for control circuit devices |
| Minimum order   | 1 Pcs                                         |
| Document ID     | EO-910B78A1E8                                 |
| Generated       | 2026-08-02                                    |

## Product Overview

Led Block P9PLNVNG  
P9PLNVNG LED block

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                             |
|--------------|-----------------------------|
| Catalog path | ABB > Command and signaling |
|--------------|-----------------------------|

## Additional Product Information

**Ordering**

Minimum Order Quantity 10 piece  
Customs Tariff Number 8539520000

**Popular Downloads**

Data Sheet, Technical Information 1SFC151007C02\_\_  
Instructions and Manuals 1SFC151011M0201

**Dimensions**

Product Net Width 9.8 mm  
Product Net Height 39.5 mm  
Product Net Depth / Length 56 mm  
Product Net Weight 0.03 kg

**Technical**

Ambient Air Temperature Operation -30 ... 70 °C  
Storage -40 ... +70 °C  
Color Yellow

Illumination Illuminated  
Lamp Type 230 V AC, integrated LED  
Function Permanent  
Mounting Type Front mounting  
Pollution Degree 3  
Rated Frequency (f) 50 / 60 Hz  
Rated Operational Voltage 230 V AC  
Connecting Capacity Flexible with Ferrule 1 x 0.75...2.5 mm<sup>2</sup>  
Flexible with Ferrule 2 x 0.75...2.5 mm<sup>2</sup>  
Flexible with Insulated Ferrule 1 x 0.75...2.5 mm<sup>2</sup>  
Flexible with Insulated Ferrule 2 x 0.75...2.5 mm<sup>2</sup>  
Flexible 1 x 0.75 ... 2.5 mm<sup>2</sup>  
Flexible 2 x 0.75 ... 2.5 mm<sup>2</sup>  
Solid 1 x 0.75...2.5 mm<sup>2</sup>  
Solid 2 x 0.75...2.5 mm<sup>2</sup>  
Connection Type Screw Clamp  
Terminal Type Screw Terminals  
Tightening Torque 0.9 N·m  
Wire Stripping Length 8 mm  
Technical UL/CSA  
Connecting Capacity UL/CSA 1x 18...14 AWG  
2x 18...14 AWG  
Environmental  
Degree of Protection Terminals IP20  
Material Compliance  
Conflict Minerals Reporting Template (CMRT) 9AKK108467A5658  
REACH Declaration 2CMT2022-006479  
RoHS Declaration 2CMT2022-006498  
RoHS Information Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019  
Toxic Substances Control Act - TSCA 2CMT2023-006523  
WEEE B2C / B2B Business To Business  
WEEE Category 5. Small Equipment (...)

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SFA197014R1073 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.