

**INDUSTRIAL COMPONENT DATA**

# 1SFA619100R1118 ABB Compact illuminated pushbutton CP1-11C-10

**Brand: ABB | Manufacturer Part Number: 1SFA619100R1118**

|                 |                       |
|-----------------|-----------------------|
| Manufacturer    | ABB                   |
| MPN / Reference | 1SFA619100R1118       |
| Catalog number  | 619100                |
| Category        | Push button, complete |
| Minimum order   | 1 Pcs                 |
| Document ID     | EO-16E5F99022         |
| Generated       | 2026-08-01            |

## Product Overview

Compact illuminated pushbutton CP1-11C-10

CP1-11C-10 Pushbutton

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

**Catalog path**      **ABB > Command and signaling**

## Additional Product Information

**Ordering**

Minimum Order Quantity 10 piece

Customs Tariff Number 8536501999

**Popular Downloads**

Data Sheet, Technical Information 1SFC151007C02\_\_

Instructions and Manuals 1SFC151011M0201

**Dimensions**

Product Net Width 0.03 m

Product Net Height 0.03 m

Product Net Depth / Length 0.055 m

Product Net Weight 0.025 kg

**Technical**

Ambient Air Temperature Operation -25 ... +70 °C

Storage -40 ... +85 °C

Color Clear  
Actuator Type Flush  
Bezel Material Plastic  
Illumination Illuminated  
Lamp Type LED 24V AC/DC  
Function Momentary  
Number of Auxiliary Contacts NC 0  
Number of Auxiliary Contacts NO 1  
Enclosure Type NEMA Type1  
Type12  
Type13  
Type3R  
Type4  
Type4X  
Pollution Degree 3  
Rated Insulation Voltage (Ui) 300 V  
Rated Impulse Withstand Voltage (Uimp) 6 kV  
Rated Frequency (f) 50 / 60 Hz  
Supply Circuit 50 / 60 Hz  
Rated Operational Voltage 24 V AC/DC  
Supply Circuit 24 V AC/DC  
Rated Operational Current DC-13 (Ie) (24 V) 0.3 A  
(125 V) 0.2 A  
Rated Operational Current AC-15 (Ie) (240 V) 2 A  
(220 / 240 V) 2 A  
Power Loss Maximum 2.5 W  
Mechanical Durability 0.5 million  
Connecting Capacity Flexible with Ferrule 1 x 0.5...1.5 mm<sup>2</sup>  
Flexible with Ferrule 2 x 0.5...1.5 mm<sup>2</sup>  
Flexible with Insulated Ferrule 1 x 0.5...1.5 mm<sup>2</sup>  
Flexible with Insulated Ferrule 2 x 0.5...1.5 mm<sup>2</sup>  
Flexible 1 x 0.5 ...1.5 mm<sup>2</sup>  
Flexible 2 x 0.5 ...1.5 mm<sup>2</sup>  
Solid 1 x 0.5...1.5 mm<sup>2</sup>  
Solid 2 x 0.5...1.5 mm<sup>2</sup>  
Connection Type Screw Clamp  
Terminal Type Screw Terminals  
Tightening Torque 0.8 N·m  
Wire Stripping Length 6 mm  
Technical UL/CSA  
Connecting Capaci...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SFA619100R1118 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.