

INDUSTRIAL COMPONENT DATA

1SFL431022R8400 ABB UA95-30-00 CONDENS CONT. 60kVAr 100V50Hz

Brand: ABB | Manufacturer Part Number: 1SFL431022R8400



Manufacturer	ABB
MPN / Reference	1SFL431022R8400
Catalog number	431022
Category	Capacitor contactor
Minimum order	1 Pcs
Document ID	EO-FCB88036FF
Generated	2026-08-06

Product Overview

UA95-30-00 CONDENS CONT. 60kVAr 100V50Hz
UA95-30-00 110V 50Hz / 110-120V 60Hz Contactor

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Contactors and overload relays

Additional Product Information

Ordering

Minimum Order Quantity 1 piece

Customs Tariff Number 85364900

Popular Downloads

Data Sheet, Technical Information 1SBC100214C0202

Instructions and Manuals 5309660-60

CAD Dimensional Drawing 2CDC001079B0201

Dimensions

Product Net Width 90 mm

Product Net Depth / Length 123.5 mm

Product Net Height 148 mm

Product Net Weight 1.8 kg

Technical

Number of Main Contacts NO 3

Number of Main Contacts NC 0

Number of Auxiliary Contacts NO 0

Number of Auxiliary Contacts NC 0

Number of Poles 3P

Rated Operational Voltage Main Circuit 1000 V

Rated Frequency (f) Main Circuit 50 / 60 Hz

Conventional Free-air Thermal Current (I_{th}) acc. to IEC 60947-4-1, Open Contactors ? = 40 °C 145 A

Rated Operational Power AC-3 (P_e) (380 / 400 V) 45 kW

Rated Operational Power AC-6b (P_e) (230 / 240 V) 40 °C, 50 / 60 Hz 35 kvar

(230 / 240 V) 55 °C, 50 / 60 Hz 35 kvar

(230 / 240 V) 70 °C, 50 / 60 Hz 30 kvar

(400 / 415 V) 40 °C, 50 / 60 Hz 65 kvar

(400 / 415 V) 70 °C, 50 / 60 Hz 55 kvar

(400 / 415 V) 55 °C, 50 / 60 Hz 65 kvar

(440 V) 40 °C, 50 / 60 Hz 65 kvar

(440 V) 55 °C, 50 / 60 Hz 65 kvar

(440 V) 70 °C, 50 / 60 Hz 55 kvar

(500 / 550 V), 40 °C, 50 / 60 Hz 70 kvar

(500 / 550 V) 55 °C, 50 / 60 Hz 70 kvar

(500 / 550 V) 70 °C, 50 / 60 Hz 60 kvar

(690 V) 40 °C, 50 / 60 Hz 80 kvar

(690 V) 55 °C, 50 / 60 Hz 80 kvar

(690 V) 70 °C, 50 / 60 Hz 70 kvar

Rated Short-time Withstand Current Low Voltage (I_{cw}) at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 800 A
at 40 °C Ambient Temp, in Free Air, from a Co...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SFL431022R8400 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.