

INDUSTRIAL COMPONENT DATA

XLP1 1SEP101912R0004 ABB 250 A incl. A40/120 adapter incl. 3xM10 bolts, cable above

Brand: ABB | Manufacturer Part Number: XLP1



Manufacturer	ABB
MPN / Reference	XLP1
Catalog number	1SEP101912R0004
Category	Fuse switch disconnecter
Minimum order	1 Pcs
Document ID	EO-8A424627A9
Generated	2026-08-04

Product Overview

250 A incl. A40/120 adapter incl. 3xM10 bolts, cable above

XLP1-A40/120-A-3M10

XLP1-A40/120-A-3M10-above Fuse Switch Disconnecter

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **ABB > Manual Switches > XLP, SLP**

Additional Product Information

Material Compliance

Conflict Minerals Reporting Template (CMRT) 9AKK108467A5658

REACH Declaration 1SCC011021D0201

RoHS Declaration 1SCC011020D0201

RoHS Information Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Popular Downloads

Data Sheet, Technical Information 1SEC312012D0201

Environmental

Degree of Protection IP30

Ordering

Minimum Order Quantity 1 piece

Customs Tariff Number 85389099

Country or Territory of Origin Bulgaria

Dimensions

Product Net Width 185 mm

Product Net Height 270 mm

Product Net Depth / Length 196 mm

Product Net Weight 2.75 kg

Container Information

Package Level 1 Units shrink-wrap 1 piece

Package Level 1 Width 185 mm

Package Level 1 Depth / Length 196 mm

Package Level 1 Height 270 mm

Package Level 1 Gross Weight 2.75 kg

Package Level 1 EAN 7025840016496

Package Level 2 EAN 7025840016496

Technical

Degree of Protection IP30

Device Type Manager (DTM) Fuseswitchdisconnector

Electronic Fuse Monitoring No

Fuse Size NH1

Fuse System DIN

Fuse Type NH

Handle Type Front cover 3P

Mounting Type 40mm Busbar System

Number of Poles 3P

Rated Conditional Short-Circuit Current (Inc) (690 V) 50 kiloampere rms

Rated Current (In) 250 A

Rated Frequency (f) Main Circuit 50/60 Hz

Rated Impulse Withstand Voltage (Uimp) Main Circuit 8 kV

Rated Operational Current AC-21B (Ie) (690 V) 200 A

Rated Operational Current AC-22B (Ie) (500 V) 250 A

Rated Operational Voltage 500 V AC

690 V AC

Rated Voltage (Ur) 500 V AC

690 V AC

Special Functions Not Included

Standar...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEWSend ABB / XLP1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.