

INDUSTRIAL COMPONENT DATA

2CCG001252R0001 ABB Int. aut. S801P-K125 1p 125A K 50kA

Brand: ABB | Manufacturer Part Number: 2CCG001252R0001



Manufacturer	ABB
MPN / Reference	2CCG001252R0001
Catalog number	2CCG001252R0001
Category	Miniature circuit breaker (MCB)
Minimum order	1 Pcs
Document ID	EO-10419A6BF9
Generated	2026-08-05

Product Overview

Int. aut. S801P-K125 1p 125A K 50kA

S801P-K125 High Performance Circuit Breaker. K Characteristic. 50kA, 125A, 1P

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Industrial

Additional Product Information

ABB EcoSolutions

ABB EcoSolutions Yes

EcoSolutions Profile 9AKK108471A1082

Recyclability Rate of the Product acc. to EN45555 Design for Closing Resource Loops - Standard EN45555 - 86.29 %

ABB Site Meeting Group Waste To Landfill Target No non-hazardous waste is sent to a landfill

End Of Life Disassembling Instructions 9AKK108470A2575

Environmental Product Declaration - EPD 9AKK108470A1695

9AKK108470A1696

Technical

Rated Ultimate Short-Circuit Breaking Capacity (Icu) (240 V AC) 50 kA

(254 V AC) 30 kA

(289 / 500 V AC) 10 kA

(400 V AC) 4.5 kA

(125 V DC) 30 kA

Rated Service Short-Circuit Breaking Capacity (Ics) (240 / 415 V AC) 40 kA

Contact Position Indication ON / OFF / TRIP
Energy Limiting Class 3
Number of Protected Poles 1
Number of Poles 1P
Tightening Torque 3.5 N·m
Release Type K
Actuator Marking I / O
Recommended Screw Driver Pozidriv 2
Accessories Available Yes
Connecting Capacity Flexible 1...50 mm²
Rigid 1...70 mm²
Wire Stripping Length 19 mm
Electrical
Tripping Characteristic K
Rated Operational Voltage acc. to IEC 60898-1 230 V AC
acc. to IEC 60947-2 400 V AC
Rated Insulation Voltage (Ui) acc. to IEC/EN 60664-1 690 V
Rated Impulse Withstand Voltage (Uimp) 6 kV
Input Voltage Type AC/DC
Rated Current (In) 125 A
Rated Short-Circuit Capacity (230 / 400 V AC) 15 kA
Frequency (f) 50/60 Hz
Rated Frequency (f) 50/60 Hz
Power Loss Total 9.4 W
at Rated Operating Conditions per Pole 9.4 W
Overvoltage Category III
Material Compliance
RoHS Declaration 9AKK108468A0836
RoHS Inform...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 2CCG001252R0001 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.