

INDUSTRIAL COMPONENT DATA

2CDS383001R0405 ABB Int.aut. S303P-B40 3p 40A B 25kA

Brand: ABB | Manufacturer Part Number: 2CDS383001R0405



Manufacturer	ABB
MPN / Reference	2CDS383001R0405
Catalog number	383001
Category	Miniature circuit breaker (MCB)
Minimum order	1 Pcs
Document ID	EO-60F7E0FC74
Generated	2026-08-04

Product Overview

Int.aut. S303P-B40 3p 40A B 25kA

Miniature Circuit Breaker - S300P - 3P - 40 A - B - (AC) 20 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Industrial

Additional Product Information

ABB EcoSolutions

ABB EcoSolutions Yes

EcoSolutions Profile 9AKK108469A3274

Recyclability Rate of the Product acc. to EN45555 Design for Closing Resource Loops - Standard EN45555 - 63.8 %

Improved Energy Efficiency for Customers Product Efficiency - Product requires less energy to operate compared to similar product on market or older products from the same line

Extended Product Lifetime Product Durability

End Of Life Disassembling Instructions 9AKK108467A9801

Environmental Product Declaration - EPD 9AKK108467A7130

Technical

Dielectric Test Voltage 50 / 60 Hz - 1 min 2 kV

Rated Ultimate Short-Circuit Breaking Capacity (Icu) (415 V AC) 25 kA

(440 V AC) 15 kA

(400 V) 25 kA

Power Supply Connection Arbitrary

Contact Position Indication Red ON / Green OFF
Electrical Endurance 10000 AC cycle
Mechanical Endurance 20000 cycle
Number of Protected Poles 3
Number of Poles 3P
Tightening Torque 2.8 N·m
Actuator Type Toggle
Screw Terminal Type Failsafe Bi-directional Cylinder-lift Terminal
Actuator Marking I / O
Actuator Material Insulation Group II, Black, Sealable
Recommended Screw Driver Pozidriv 2
Accessories Available Yes
Connecting Capacity Busbar 10/10 mm²
Flexible with Ferrule 0.75 ... 25 mm²
Flexible 0.75 ... 25 mm²
Flexible 0.75 ... 25 mm²
Rigid 0.75 ... 35 mm²
Stranded 0.75 ... 35 mm²
Installation Size acc. to DIN 43880 1
Wire Stripping Length 14 mm
Terminal Type Screw Terminals
Electrical
Tripping Characteristic B
Rated Operational Voltage acc. to IEC 60898-1 415 V AC
acc. to I...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 2CDS383001R0405 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.