

INDUSTRIAL COMPONENT DATA

2CMA142435R1000 ABB Int. Boxed disconnecter KSF225DP

Brand: ABB | Manufacturer Part Number: 2CMA142435R1000



Manufacturer	ABB
MPN / Reference	2CMA142435R1000
Catalog number	142435
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-4873C99142
Generated	2026-08-02

Product Overview

Int. Boxed disconnecter KSF225DP
KSF225DP Fireman switch

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	ABB > Manual Switches
--------------	-----------------------

Additional Product Information

Material Compliance

Conflict Minerals Reporting Template (CMRT) 9AKK108467A5658

REACH Declaration 1SCC340076D0201

RoHS Declaration 1SCC340075D0201

RoHS Information Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Toxic Substances Control Act - TSCA 1SCC340095D0201

Popular Downloads

Data Sheet, Technical Information CMC300001D0002

Instructions and Manuals 9AKK108467A6812

Mechanical Drawings LBA1R131160DM25.stp

Environmental

Degree of Protection acc. to IEC 60529 IP65

Ordering

Minimum Order Quantity 1 piece

Customs Tariff Number 85363030

Country or Territory of Origin Bulgaria

Dimensions

Product Net Width 111 mm

Product Net Height 130 mm

Product Net Depth / Length 60 mm

Product Net Weight 0.57 kg

Container Information

Package Level 1 Units box 1 piece

Package Level 1 Width 112 mm

Package Level 1 Depth / Length 131 mm

Package Level 1 Height 62 mm

Package Level 1 Gross Weight 0.57 kg

Package Level 1 EAN 7392696424356

Technical

Cable Cross-Section 0.75 ... 10 mm²

Cable Entry Position Top and/or Bottom

Cable Outlets Per Side 2xM25 / 2xM25

Connecting Capacity Main Circuit Screw Clamp 0.75 ... 10 mm²

Screw Clamp / PE Terminal 1pc, 0.75 ... 10 mm²

Conventional Free-air Thermal Current (I_{th}) 25 A

Conventional Thermal Current (I_{th}) Fully Enclosed 25 A

Degree of Protection acc. to IEC 60529 IP65

Enclosure Material Aluminium

Handle Color Black

Handle Type Side-operated handle

Impact Resistance Rating Housing IK09

Maximum Mounted Auxiliary Contacts 1 NO, 0 NC

Mounted...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 2CMA142435R1000 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.