

INDUSTRIAL COMPONENT DATA

2CPX052201R9999 ABB CA23VT Arm.superf.72mod(125mm) pta.tra.

Brand: ABB | Manufacturer Part Number: 2CPX052201R9999



Manufacturer	ABB
MPN / Reference	2CPX052201R9999
Catalog number	052201
Category	Small distribution board
Minimum order	1 Pcs
Document ID	EO-D9D790B368
Generated	2026-08-02

Product Overview

CA23VT Arm.superf.72mod(125mm) pta.tra.

compact distribution boards, partly assembled cabinet, for the internal use, with Door, class of protection II (double insulated), in combination with earthing set (accessory) we can achieve protection class 1, degree of protection IP44, applicable standards: EN 61439-1, EN 61439-3, Rated operational voltage 400V AC 50/60 Hz, rated current 125 A, powder-coated, in RAL 9016, enclosure out of sheet steel, transparent door, door out of sheet steel, in RAL 9016, with Standard closure, door opening angle 120 degree, door hinge right or left, cable entry on top via membrane flange mounted, on bottom via flange opening pre-punched, dimensions in mm (H x W x D): 500 x 550 x 160, Grid unit 3 GU, panel width 2, 3-rows, Space units 72, Row distance in mm: 125, covers out of Plastic, 90 degree press and turn closure, RAL 7035, with N/PE Quick-terminal, cable fastening rail integrated, expanded with distributor fields, device support removable

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

ABB > Boxes and cabinets

Additional Product Information

b'
General Information
Extended Product Type:CA23VTProduct ID:2CPX052201R9999EAN:4011617522010Catalog Description:CA23VT Comp.DB 2PW 3R trans.doorLong Description:compact distribution boards, partly assembled cabinet, for the internal use, with Door, class of protection II (double insulated), in combination with earthing set (accessory) we can achieve protection class 1, degree of protection IP44, applicable standards: EN 61439-1, EN 61439-3, Rated operational voltage 400V AC

50/60 Hz, rated current 125 A, powder-coated, in RAL 9016, enclosure out of sheet steel, transparent door, door out of sheet steel, in RAL 9016, with Standard closure, door opening angle 120 degree, door hinge right or left, cable entry on top via membrane flange mounted, on bottom via flange opening pre-punched, dimensions in mm (H x W x D): 500 x 550 x 160, Grid unit 3 GU, panel width 2, 3-rows, Space units 72, Row distance in mm: 125, covers out of Plastic, 90 degree press and turn closure, RAL 7035, with N/PE Quick-terminal, cable fastening rail integrated, expanded with distributor fields, device support removable

EAN:4011617522010 Minimum Order Quantity:1 piece Customs Tariff Number:85381000 Dimensions

Product Net Width:550 mm Product Net Height:500 mm Product Net Depth / Length:160 mm Product Net Weight:11.961 kg Container Information

Package Level 1 Units:pack 1 piece Package Level 1 Width:556.000 mm Package Level 1 Height:502.000 mm Package Level 1 Depth / Length:165.000 mm Package Level 1 Gross...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 2CPX052201R9999 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.