

## INDUSTRIAL COMPONENT DATA

## 2CSF204568R1630 ABB Int.dif.F204B-63/0.03 4p 63 B 30mA

Brand: ABB | Manufacturer Part Number: 2CSF204568R1630



|                 |                                         |
|-----------------|-----------------------------------------|
| Manufacturer    | ABB                                     |
| MPN / Reference | 2CSF204568R1630                         |
| Catalog number  | 204568                                  |
| Category        | Residual current circuit breaker (RCCB) |
| Minimum order   | 1 Pcs                                   |
| Document ID     | EO-90FAC7F8C9                           |
| Generated       | 2026-08-01                              |

## Product Overview

Int.dif.F204B-63/0.03 4p 63 B 30mA

Residual Current Circuit Breaker F200 - 4P - 30 mA - 63 A - Type B

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification &amp; Catalog Path

Catalog path ABB &gt; Industrial

## Additional Product Information

ABB EcoSolutions

ABB EcoSolutions Yes

EcoSolutions Profile 9AKK108469A3795

Recyclability Rate of the Product acc. to EN45555 Design for Closing Resource Loops - Standard EN45555 - 77.05 %

ABB Site Meeting Group Waste To Landfill Target No non-hazardous waste is sent to a landfill

UL 2799 Zero Waste To Landfill Validation available

Sustainable Material Content in Packaging (wt. %) Recycled Cardboard - 29.08 %

Recycled Cardboard - 61.23 %

Recycled Cardboard - 2.66 %

Recycled Paper - 0 %

Recycled Paper - 0 %

Extended Product Lifetime Product Durability

Offered with Takeback Services Take Back for Recycling

End Of Life Disassembling Instructions 9AKK108470A1744

Environmental Product Declaration - EPD 9AKK108468A5757

**Technical**

Type of Residual Current Type B  
Test Voltage (Ut) 170 ... 253 V  
Dielectric Test Voltage 2500 kV  
Impulse Current I (max, 8 / 20  $\mu$ s) 3000 A  
Maximum Surge Current 3 kA  
Leakage Current Type B  
Electrical Endurance 10000 cycle  
Mechanical Endurance 20000 cycle  
Number of Poles 4P  
Number of Modular Spacings per DIN Rail 4  
Operating Characteristic 10ms Delay (High Immunity)  
Position of Neutral Terminals Right  
Tightening Torque 2.8 N·m  
Delay Time (?) 10 ms  
Accessory Type Auxiliary contact  
Signal contact/auxiliary contact  
Shunt trip  
Undervoltage release  
Overvoltage release  
Motor operating device  
Auto reclosing unit  
Actuator Type Toggle - Insulation group I - II, RAL 5015  
Housing Type Insulation group I - II, RAL 7035  
Screw Terminal Type Failsafe Bi-directional Cylinder...

**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**

Send ABB / 2CSF204568R1630 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.