

INDUSTRIAL COMPONENT DATA

2CSF204568R3630 ABB Int.dif.F204B-63/0.3 4p 63 B 300mA

Brand: ABB | Manufacturer Part Number: 2CSF204568R3630



Manufacturer	ABB
MPN / Reference	2CSF204568R3630
Catalog number	204568
Category	Residual current circuit breaker (RCCB)
Minimum order	1 Pcs
Document ID	EO-837EB828D6
Generated	2026-07-29

Product Overview

Int.dif.F204B-63/0.3 4p 63 B 300mA

Residual Current Circuit Breaker F200 - 4P - 300 mA - 63 A - Type B

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Industrial

Additional Product Information

ABB EcoSolutions

ABB EcoSolutions Yes

EcoSolutions Profile 9AKK108469A3795

Recyclability Rate of the Product acc. to EN45555 Design for Closing Resource Loops - Standard EN45555 - 77.05 %

ABB Site Meeting Group Waste To Landfill Target No non-hazardous waste is sent to a landfill

UL 2799 Zero Waste To Landfill Validation available

Sustainable Material Content in Packaging (wt. %) Recycled Cardboard - 29.08 %

Recycled Cardboard - 61.23 %

Recycled Cardboard - 2.66 %

Recycled Paper - 0 %

Recycled Paper - 0 %

Extended Product Lifetime Product Durability

Offered with Takeback Services Take Back for Recycling

End Of Life Disassembling Instructions 9AKK108470A1744

Environmental Product Declaration - EPD 9AKK108468A5757

Technical

Type of Residual Current Type B
Test Voltage (Ut) 110 ... 253 V
Dielectric Test Voltage 2500 kV
Impulse Current I (max, 8 / 20 μ s) 3000 A
Maximum Surge Current 3 kA
Leakage Current Type B
Electrical Endurance 10000 cycle
Mechanical Endurance 20000 cycle
Number of Poles 4P
Number of Modular Spacings per DIN Rail 4
Operating Characteristic 10ms Delay (High Immunity)
Position of Neutral Terminals Right
Tightening Torque 2.8 N·m
Delay Time (?) 10 ms
Accessory Type Auxiliary contact
Signal contact/auxiliary contact
Shunt trip
Undervoltage release
Overvoltage release
Motor operating device
Auto reclosing unit
Actuator Type Toggle - Insulation group I - II, RAL 5015
Housing Type Insulation group I - II, RAL 7035
Screw Terminal Type Failsafe Bi-directional Cylinder...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 2CSF204568R3630 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.