

## INDUSTRIAL COMPONENT DATA

## 2CSF304131R3630 ABB Reconec. Dif. Aut. FARI4TestA63/0.3

Brand: ABB | Manufacturer Part Number: 2CSF304131R3630



|                 |                                                               |
|-----------------|---------------------------------------------------------------|
| Manufacturer    | ABB                                                           |
| MPN / Reference | 2CSF304131R3630                                               |
| Catalog number  | 304131                                                        |
| Category        | Residual current circuit breaker (RCCB) with auxiliary device |
| Minimum order   | 1 Pcs                                                         |
| Document ID     | EO-3866BAFAB6                                                 |
| Generated       | 2026-08-02                                                    |

### Product Overview

Reconec. Dif. Aut. FARI4TestA63/0.3

Autoreclosing device with Automatic Test F-ARI Test - 4P - 300 mA - 63 A - Type A

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

|              |                  |
|--------------|------------------|
| Catalog path | ABB > Industrial |
|--------------|------------------|

### Additional Product Information

## Technical

Type of Residual Current Type A

Rated Service Short-Circuit Breaking Capacity (Ics) 1 kA

Maximum Surge Current 3 kA

Leakage Current Type A

Number of Poles 4P

Operating Characteristic Instantaneous

Position of Neutral Terminals Right

Rated Cross-Section 1 - Solid-Core 1 ... 35 mm<sup>2</sup>4 - Multi-Wired 1 ... 35 mm<sup>2</sup>

## Electrical

Rated Voltage (Ur) 400 V

Rated Operational Voltage 230 ... 400 V AC

Rated Insulation Voltage (Ui) 500 V

Rated Impulse Withstand Voltage (Uimp) 4 kV

Rated Current (In) 63 A  
Rated Residual Current 300 mA  
Rated Conditional Short-Circuit Current (Inc) 10 kA  
Rated Frequency (f) 50 Hz  
Power Loss Total 12 W  
Material Compliance  
RoHS Declaration 9AKK106930A2452  
RoHS Information Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019  
RoHS Date 20200527  
REACH Information No data - If REACH inform is not yet available for a certain product  
Conflict Minerals Reporting Template (CMRT) 9AKK108468A3363  
WEEE Category 5. Small Equipment (No External Dimension More Than 50 cm)  
WEEE B2C / B2B Business To Consumer  
Environmental  
Ambient Temperature -25...60 °C  
Ambient Air Temperature Operation -25...60 °C  
Degree of Protection IP20  
Pollution Degree 2  
Environmental Information Refer to Declaration of Conformity CE  
Dimensions  
Width in Number of Modular Spacings 7  
Product Net Width 125 mm  
Product Net Height 115 mm  
Product Net Depth / Length 80 mm  
Product Net Weight 880 g  
Built-In Depth (t2) 80 mm  
Engineering  
EPLAN Data 9AAC187566\_EPLAN  
Ordering  
Package Level 1....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 2CSF304131R3630 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.