

INDUSTRIAL COMPONENT DATA

2CSR245080R1324 ABB I.com.DS200L 1p+N C 32A AC 6kA 30mA

Brand: ABB | Manufacturer Part Number: 2CSR245080R1324



Manufacturer	ABB
MPN / Reference	2CSR245080R1324
Catalog number	245080
Category	Earth leakage circuit breaker
Minimum order	1 Pcs
Document ID	EO-4C14737D84
Generated	2026-08-04

Product Overview

I.com.DS200L 1p+N C 32A AC 6kA 30mA

The DS201 series is a 1P+N RCBO in two-modules width for the protection of end user single-phase circuits against overload and short-circuit currents; protection against the effects of sinusoidal alternating earth fault currents; protection against indirect contacts and additional protection against direct contacts (with sensitivity = 30 mA).

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Tertiary / Industrial

Additional Product Information

b'
General Information
Extended Product Type:DS201 L C32 AC30Product ID:2CSR245080R1324EAN:8012542637615Catalog
Description:DS201 L C32 AC30 - RCBOLong Description:The DS201 series is a 1P+N RCBO in two-modules width for the protection of end user single-phase circuits against overload and short-circuit currents; protection against the effects of sinusoidal alternating earth fault currents; protection against indirect contacts and additional protection against direct contacts (with sensitivity = 30 mA).\nTechnical
Standards:IEC/EN 61009-1, IEC/EN 61009-2-1Type of Residual Current:AC typeNumber of Poles:2Number of Protected Poles:1Rated Current (In):32 ARated Current Sensitivity:0.03 ARated Voltage (Ur):230 VRated Insulation Voltage (Ui):500 VOvervoltage Category:IIIPollution Degree:2Test Voltage (Ut):170 ... 264 VRated Frequency (f):50 ... 60 HzRated Short-Circuit Capacity (Icn):4.5 kARated Ultimate Short-Circuit Breaking Capacity (Icu):6 kARated Service Short-Circuit Breaking Capacity (Ics):4.5 kARated Residual Breaking Capacity (I?m):EN 61009-1 4500 A

IEC 61009-1 4500 A Primary Rated Impulse Withstand Voltage: 4 kV Dielectric Test Voltage: 2.5 kV Tripping
Characteristic: C Energy Limiting Class: 3 Housing Type: Insulation group I - II, RAL 7035 Actuator Type: Toggle - Insulation
group II, Black RAL 9005, sealable in ON-OFF positions Contact Position Indication: Red ON / Green OFF Fault
Indication: Blue flag on toggle Electrical Endurance: 10000 cycle Mechanical Endurance (Nendu): 20000 cycle Degree...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 2CSR245080R1324 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.