

INDUSTRIAL COMPONENT DATA

2CSR255163R1064 ABB I.com.DS301C 1p+N C 6A A 10kA 30mA

Brand: ABB | Manufacturer Part Number: 2CSR255163R1064



Manufacturer	ABB
MPN / Reference	2CSR255163R1064
Catalog number	255163
Category	Earth leakage circuit breaker
Minimum order	1 Pcs
Document ID	EO-AD6DA6A618
Generated	2026-08-01

Product Overview

I.com.DS301C 1p+N C 6A A 10kA 30mA

DS301C C6 A30 Residual Current Circuit Breaker with Overcurrent Protection

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Tertiary / Industrial

Additional Product Information

Extended Product Type:DS301C C6 A30

Product ID:2CSR255163R1064

EAN:8012542360957

Catalog Description:DS301C C6 A30 Residual Current Circuit Breaker with Overcurrent Protection

Long Description:The DS301C series is a 1P+N RCBO in one module width for the protection of end user single-phase circuits against overload and short-circuit currents, protection against the effects of sinusoidal alternating and direct pulsating earth fault currents, protection against indirect contacts and additional protection against direct contacts (with sensitivity = 30 mA)

+-Accessories

Identifier Description Type Qty Unit Of Measure

GJF1101903R0004

SA1E Terminals and Installation Material SA1E 1 piece

GJF1101903R0002

SA2 Terminals and Installation Material SA2 1 piece

GJF1109999R0001
SA2I Terminals and Installation Material SA2I 1 piece
GJF1101903R0003
SA3 Terminals and Installation Material SA3 1 piece
2CDL210331R1012
PSc 1/24/10 N Busbar PSc 1/24/10 N 1 piece
2CDL210331R1060
PSc 1/120/10 N Busbar PSc 1/120/10 N 1 piece
2CDL230331R1012
PSc 3/24/10 N Busbar PSc 3/24/10 N 1 piece
2CDL230331R1060
PSc 3/120/10 N Busbar PSc 3/120/10 N 1 piece
2CDL200331R0003
PSc-END End Cap PSc-END 1 piece
2CDL200331R0013
BSKc Accessories for PSc Busbars BSKc 1 piece
2CDL200001R2506
AST25/27QS Feeder Terminal AST25/27QS 1 piece
Technical
Standards: IEC/EN 61009-1
IEC/EN 61009-2-1
Tripping Characteristic: C
Type of Residual Current: A type
Rated Operational Voltage: 230 / 240 V AC
Rated Insulation Voltage (Ui): 500 V
Test...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 2CSR255163R1064 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.