

INDUSTRIAL COMPONENT DATA

2CSR275180R3404 ABB I.com.DS200M 1p+N C 40A 15kA 300mA

Brand: ABB | Manufacturer Part Number: 2CSR275180R3404



Manufacturer	ABB
MPN / Reference	2CSR275180R3404
Catalog number	275180
Category	Earth leakage circuit breaker
Minimum order	1 Pcs
Document ID	EO-603CEDBD34
Generated	2026-08-05

Product Overview

I.com.DS200M 1p+N C 40A 15kA 300mA

The DS201 series is a 1P+N RCBO in two-modules width for the protection of end user single-phase circuits against overload and short-circuit currents; protection against the effects of sinusoidal alternating and direct pulsating earth fault currents; protection against indirect contacts and additional protection against direct contacts (with sensitivity = 30 mA).

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Tertiary / Industrial

Additional Product Information

b'
General Information
Extended Product Type:DS201 M C40 A300Product ID:2CSR275180R3404EAN:8012542582014Catalog
Description:DS201 M C40 A300 - RCBOLong Description:The DS201 series is a 1P+N RCBO in two-modules width for the protection of end user single-phase circuits against overload and short-circuit currents; protection against the effects of sinusoidal alternating and direct pulsating earth fault currents; protection against indirect contacts and additional protection against direct contacts (with sensitivity = 30 mA).
Technical
Standards:IEC/EN 61009-1, IEC/EN 61009-2-1Type of Residual Current:A typeNumber of Poles:2Number of Protected Poles:1Rated Current (In):40 ARated Current Sensitivity:0.3 ARated Voltage (Ur):230 VRated Insulation Voltage (Ui):500 VOvervoltage Category:IIIPollution Degree:2Test Voltage (Ut):110 ... 264 VRated Frequency (f):50 ... 60 HzRated Short-Circuit Capacity (Icn):10 kARated Ultimate Short-Circuit Breaking Capacity (Icu):15 kARated Service Short-Circuit Breaking Capacity (Ics):11.2 kARated Residual Breaking Capacity (I?m):EN 61009-1 6000 A

IEC 61009-1 4500 A Primary Rated Impulse Withstand Voltage: 4 kV Dielectric Test Voltage: 2.5 kV Tripping
Characteristic: C Energy Limiting Class: 3 Housing Type: Insulation group I - II, RAL 7035 Actuator Type: Toggle - Insulation
group II, Black RAL 9005, sealable in ON-OFF positions Contact Position Indication: Red ON / Green OFF Fault
Indication: Blue flag on toggle Electrical Endurance: 10000 cycle Mechanical Endurance (Nend...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 2CSR275180R3404 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.