

**INDUSTRIAL COMPONENT DATA**

# 2CSR772140R3065 ABB I.com.DS202CRM 2p B 6A 10kA 300mA

Brand: ABB | Manufacturer Part Number: 2CSR772140R3065



|                 |                               |
|-----------------|-------------------------------|
| Manufacturer    | ABB                           |
| MPN / Reference | 2CSR772140R3065               |
| Catalog number  | 772140                        |
| Category        | Earth leakage circuit breaker |
| Minimum order   | 1 Pcs                         |
| Document ID     | EO-F689111779                 |
| Generated       | 2026-08-01                    |

## Product Overview

I.com.DS202CRM 2p B 6A 10kA 300mA

Residual Current Circuit Breaker with Overcurrent Protection DS202CR M - 2P - Type A - 300 mA - 6 A - B

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      ABB > Tertiary / Industrial

## Additional Product Information

ABB EcoSolutions

Environmental Product Declaration - EPD 9AKK108467A5738

Technical

Type of Residual Current Type A

Test Voltage (Ut) 117...254 V

Rated Ultimate Short-Circuit Breaking Capacity (Icu) 10 kA

Rated Service Short-Circuit Breaking Capacity (Ics) 7.5 kA

Maximum Surge Current 0.25 kA

Power Supply Connection Arbitrary

Energy Limiting Class 3

Electrical Endurance 10000 operations

Mechanical Endurance 20000 operations

Number of Protected Poles 2

Number of Poles 2P

Fault Indication Blue Flag on Window  
Operating Characteristic Instantaneous  
Position of Neutral Terminals Right  
Left  
Tightening Torque 4 N·m  
Accessory Type Auxiliary contact  
Signal contact / auxiliary contact  
Earthing Switch Type Undelayed  
Accessories Available Yes  
Number of Batteries 0  
Connecting Capacity Busbar 10...10 mm<sup>2</sup>  
Flexible 1...25 mm<sup>2</sup>  
Rigid Solid 1...35 mm<sup>2</sup>  
Rated Cross-Section 1 - Solid-Core 1 ... 35 mm<sup>2</sup>  
4 - Multi-Wired 1 ... 25 mm<sup>2</sup>  
Wire Stripping Length 11 mm  
Electrical  
Tripping Characteristic B  
Rated Operational Voltage acc. to IEC 60898-1 230 V  
Rated Insulation Voltage (Ui) acc. to IEC/EN 60664-1 440 V  
Rated Impulse Withstand Voltage (Uimp) 4 kV  
Input Voltage Type AC  
Rated Current (In) 6 A  
Rated Residual Current 300 mA  
Rated Short-Circuit Capacity 10 kA  
Rated Frequency (f) 50 Hz  
Power Loss 3.04 W  
Overvoltage Category III  
Material Compliance  
RoHS Declaration 9AKK108466A5162  
RoHS Information Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019  
RoHS Date 20220211  
REACH Declaration 9AKK108467A...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 2CSR772140R3065 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.